

HD CCTV 600TVL Super Mini Pinhole CCD Camera



Features

- 1, Using the high performance sensor, image is clear and delicate;
- 2, Support IR-CUT dual filter switch, to achieve day and night monitoring, color is not partial and distortion;
- 3, Analog HD 600TVL CCD video output;
- 4, Support the ultra low illumination;
- 5, Support automatic electronic shutter function, adapt to different monitoring environment;
- 6, Input power: DC12V, ir distance 3-5m
- 7, 35*35*21mm

Accessories

- User Manual
- Warranty Card
- Screw fittings
- Desiccant

Specifications

Model WDM-I903H

Camera

Sensor 1/3" Sony4140+638 CCD

System NTSC

Resolution 600TVL

Lens 3.7/4.3/6mm

IR distance 3-5m

Video

Pixels NTSC:768x494

Scanning 2:1 Interlace

Sync Mode Internal

Horizontal/vertical Frequency PAL:15.625 kHz, 50.00 HZ / NTSC :15.734kHz,59.94HZ

Video Output 1.0Vp-p/75Ω Composite video signal

S/N Ratio >=52dB (AGC off)

D/N Dual filter switching (IR CUT)

Illumination 0.00001Lux/F1.2 (color)

Features

OSD Support NO

Menu Language EN, CN, DE, FRA, IT, ES, PL, RU, PT, NL, TR...

White Balance AUTO / MANUAL

Picture Adjustment Yes

Normal

Power DC12V

Operating Temperature -10°C-50°C

Dimension 35*35*21mm