

H.265 3.0MP Video Security Surveillance IR Bullet IP HD Camera



Features

- *Hisilicon high-performance DSP
- *High quality progressive scanning CMOS
- *H.265 High profile
- *support dual stream, support mobile phone
- *support power supply DC12V/POE
- *Standard ONVIF Protocol
- *Complete SDK for second development. Support multi network protocols
- *Provide a unified free client to achieve video recording/playback/preview
- *Support ICR filter switching function, day and night surveillance
- *Waterproof IP66

Dimension



Accessories

- User Manual
- CD
- Screw fittings

Specification

| | |
|-----------------------|---|
| Product Name | H.265 3.0MP Video Security Surveillance IR Bullet IP HD Camera |
| Model No. | WDM-IP7919S |
| Video | |
| System | Hisilicon high-performance DSP, (Hi3516CV100+SC2235P, Low lux) / (Hi3516CV100+IMX323, Starlight) / (Hi3516CV100+Sony IMX 291, Black light) for optional |
| Sensor | 1/3" 3.0M Pixels Progressive CMOS Image Sensor |
| Output resolution | 2048(H)×1536(V) |
| D/N Mode | Auto switching,black and white vide and IR cut action linkage |
| Illumination | Color 1.0Lux@F1.2,Black 0.1 Lux@F1.2 |
| Video processing | H.265 video compression, dual streaming AVI format, 0.1M~6Mbps adjustable; |
| Video Output | Main streaming: 2048*1536,1920*1080, 1280*960,1280*720, 1024*768,1280*720; Sub streaming: 960*540,640*360,480*270,352*288,320*240,352*192, 320*192,288*192,256*192 |
| Frame rate | 3.0MP 25/30 frame(full real time),support 1~30frame/seconds adjustable |
| Network interface | RJ45 ethernet,10/100M;RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP protocol supported |
| Access Protocol | Standard ONVIF Protocol, Support third party access; PC; Support IE6.0 and aboveSmartphone Support Android\iPhone |
| Lens | |
| Lens | 3.6/6mm lens |
| IR distance | 30m(36pcs f5 IR leds) |
| Function | |
| Function | Support WEB configuration, OSD,real-time video transmission Support motion detection Support front end storage ,playback and download Support uniform client and platform system application Support complete SDK for second development. |
| Normal | |
| Power supply | DC12V/POE(optional) |
| Operation temperature | -10°C~+60°C,10%~90%RH |