

China Supplier 4.0 Megapixel 4" IR Dome IP CCTV Camera



**Features**

- \*Hisilicon high-performance DSP
- \*High quality progressive scanning CMOS
- \*H.265 High profile
- \*support dual stream, support mobile phone
- \*support power supply DC12V/POE
- \*Standard ONVIF Protocol
- \*Complete SDK for second development. Support multi network protocols
- \*Provide a unified free client to achieve video recording/playback/preview
- \*Support ICR filter switching function, day and night surveillance
- \*Metal case

**Dimension**



**Accessories**

- User Manual
- CD
- Screw fittings

**Specification**

Product Name	China Supplier 4.0 Megapixel 4" IR Dome IP CCTV Camera
Model No.	WDM-IP8736D
<b>Video</b>	
System	Hisilicon high-performance DSP, Hi3516D+OV4689
Sensor	1/3" 4.0M Pixels Progressive OV4689 CMOS Image Sensor
Output resolution	2592(H)×1520(V)
D/N Mode	Auto switching,black and white vide and IR cut action linkage
Illumination	Color 1.0Lux@F1.2,Black 0.1 Lux@F1.2
Video processing	H.265 video compression, dual streaming AVI format, 0.1M~6Mbps adjustable;
Video Output	Main streaming: 2592*1520, 2018*1536, 1920*1080, 1280*960, 1280*720, 1024*768, 1280*720; Sub streaming: 960*540, 640*360, 480*270, 352*288, 320*240, 352*192, 320*192, 288*192, 256*192
Frame rate	4.0MP 25/30 frame(full real time),support 1~30frame/seconds adjustable
Network interface	RJ45 ethernet, 10/100M; RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP protocol supported
Access Protocol	Standard ONVIF Protocol, Support third party access; PC; Support IE6.0 and aboveSmartphone Support Android/iPhone
<b>Lens</b>	
Lens	3.6mm fixed lens
IR distance	20m(24pcs f5 IR leds)
<b>Function</b>	
Function	Support WEB configuration, OSD,real-time video transmission
	Support motion detection
	Support front end storage ,playback and download
	Support uniform client and platform system application
	Support complete SDK for second development.
<b>Normal</b>	
Power supply	DC12V/POE(optional)
Operation temperature	-10°C~+60°C, 10%~90%RH