



- * Support 64chs 4K1 Video access storage
- * Support H.265+/H.265/H.264, support iS super protocol, plug and play.
- * Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc
- * Support ONVIF Protocol; support GB28181 Protocol (Optional)
- * Support WEB, CMS, VMS, MYEYE Platform, provide SDK for develop
- * Support Mobile Phone Monitoring (IOS, Android)
- * Cloud Services, P2P, Alarm Information Push To Phone
- * Supports max 8channels intelligent analysis locally (target counting, item detection, area detection, virtual warning line)

Specifications

Product Name	Wdm Security 2U 64chs 4K Network Security NVR
Model No.	WDM-NVR88649MD

Video and Audio

Network video input	64chs network compressed video input (MAX:4K)
Access bandwidth	300M
Audio input	IPC compound audio input
HDMI/Output	1*HDMI, 1*VGA, Resolution: 3840×2160/30Hz, 1920×1080/60Hz, 1280×1024/60Hz
Audio output	1*RCA
Video compression	H.265/H.264 /MJPEG
Resolution	12M/8M/5M/3M/1080P/720P
Playback	4*4K; 16*1080P

Management

Record/Screenshot mode	Manual>Timing>Event>Motion detection>Alarm>Motion detect or Alarm>Motion detect and Alarm
Playbac mode	Instant playback, regular playback, event playback, external file playback, log playback
Storage mode	HDD Storage, Network Storage
Backup	General backup, event backup, Video clip backup

Interface

Ethernet	2*10/100Mbps Ethernet port, RJ45 port
serial interface	Full duplex standard RS-485 interface
Alarm In/Out	4/4
Audio In/Out	1/1
USB	3*USB, 1 USB2.0 interface front, 1 USB2.0+1 USB3.0 interface post
HDD	9*SATA interface + 1*eSATA(Up to 8TB)

Network

Networking protocol	ONVIF, IPv4, UPnP, NTP, SADP, PPoE, DHCP, etc
---------------------	---

General

Power supply	110-220V~ 50/60Hz 200W
Consumption	<30W (Without HDD)
Working temperature	0 °C - + 55 °C
Working humidity	10% -90% RH
Chassis	NVR: 440mmx432mmx90mm Package: 539mmx550mmx225mm
Weight(without HDD)	Net weight: 7.4 kg; package: 9.8kg