

H.265 4.0MP CCTV Video Surveillance IR Bullet IP HD Camera



Features

- * Hisilicon high-performance DSP
- * High quality progressive scanning CMOS
- * H.265/H.264 High profile
- * Support dual stream, support mobile phone
- * Support power supply DC12V/POE
- * Standard ONVIF Protocol, support multi network protocols
- * Metal case, Waterproof IP65

Dimension



Accessories

- User Manual
- CD
- Screw fittings

Specification		
Product Name		H.265 4.0MP CCTV Video Surveillance IR Bullet IP HD Camera
Model No.		WDM-HIP9400E
Video		
System		Hi3516D+OV4689
Sensor		1/3” 4.0M Pixels Progressive CMOS Image Sensor
Output resolution		4.0MP(2592x1520)
D/N Mode		Auto switching,black and white video and IR cut action linkage
Illumination		0.05Lux/F1.2 (Color), 0.01Lux/F1.2(B/W)
SNR		≥50db(AGC OFF)
Gain Control		Auto
DNR		3DNR
WDR		DWDR(>80dB)
Video processing		H.265/H.264 video compression, dual streaming
		32KB ~16Mbps, support VBR, CBR
Video Output	Main streaming	2592*1520,2048*1520,1920*1080,704*576,640*480,320*240
	Sub streaming	704*576,640*480,320*240
Frame rate		2592*1520(1~15fps); 2048*1520/1080P(1 ~ 25/30fps)
Network interface		RJ45 ethernet,10/100M;RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP protocol supported
Access Protocol		Standard ONVIF Protocol, Support third party access; PC;
		Support IE6.0 and above Smartphone
		Support Android\iPhone
Lens		
Lens		Standard 2.8-12 mm Manual Lens(5-50 mm Manual Lens optional)
View Angle		2.8-12 mm Manual Lens(4MP F1.3 1/3" H 91.16° - 26.4°); 5-50 mm Manual Lens(F1.6 1/4" H 33.1°-5.1°)
Function		
Function		Support WEB configuration, OSD,real-time video transmission
		Support motion detection
		Support front end storage ,playback and download
		Support uniform client and platform system application
		Support complete SDK for second development.
Normal		
Material		Metal Case, White
Weather Proof		IP65 Waterproof
Power supply		DC12V/POE(24W) optional
Operation temperature		-20°C~+60°C,10%~90%RH