

沃德镁 | IHD CCTFV Total Solution

www.wardmay.com



- * Using the high performance sensor, image is clear and delicate;
- * Support IR-CUT dual filter switch, to achieve day and night monitoring, color is not partial and distortion;
- * AHD/TVI/CVI/1200TVL 4 in 1 video output;
- * can access to many brands HD DVR;
- * Support the ultra low illumination;
- * Support automatic electronic shutter function, adapt to different monitoring environment;
- * 80 meters IR distance, DC12V
- * White, Metal, Waterproof IP66

| * White, Metal, waterproof IP66 | |
|--|--|
| Specification | |
| CCTV 4.0MP HD Video Security Surveillance IR Bullet AHD Camera | |
| WDM-AHD6253W | |
| | |
| NVP2475H+OV4689 | |
| 4.0MP(2592x1520) | |
| IR cut Auto switching | |
| 0.000LUX/F1.2(Led on) | |
| PAL: (2592x1520)@25fps | |
| NTSC: (2592x1520)@30fps | |
| PAL/NTSC | |
| AHD/TVI/CVI/CVBS standard | |
| 1CH AHD/TVI/CVI/CVBS standard Standard Singal Output(Switchable) | |
| Common 75-3 cables can be up to 500m | |
| Lens and IR | |
| 4/6/8/12mm fix iris lens | |
| 80 meters IR distance | |
| | |
| 0°~260° | |
| 5°~60° | |
| 0.5°~12° | |
| s;255 | |
| 8 groups, each group for 16 presets | |
| 4 groups, each group record 3 mins | |
| | |
| 4/25s-1/45,000s | |
| Off/Low/Medium/High/Highest | |
| Auto White Balance | |
| Support | |
| -10°C~55°C | |
| DC12V | |
| | |