



- * Using the high performance sensor, image is clear and delicate;
- * Support IR-CUT dual filter switch, to achieve day and night monitoring, color is not partial and distortion;
- * AHD/TVI/CVI/1200TVL 4 in 1 video output;
- * can access to many brands HD DVR;
- * Support the ultra low illumination;
- * Support automatic electronic shutter function, adapt to different monitoring environment;
- * 42pcs F5 ir led, 40m ir distance, DC12V
- * Metal, Waterproof IP66

Specification

| | | |
|---------------------------|---|---------------------|
| Product Name | CCTV 5.0MP HD Video Security Surveillance IR Bullet AHD Camera | |
| Model No. | WDM-AHD6213M | WDM-AHD6213Q |
| Video | | |
| Sensor | XM350+SC5239 | FH8538M+Sony IMX326 |
| Output resolution | 5.0MP(2592x1944) | |
| D/N Mode | IR cut Auto switching | |
| Minimum Illumination | 0.000LUX/F1.2(Led on) | |
| Effective Pixel | PAL: (2592x1944)@25fps | |
| | NTSC: (2592x1944)@30fps | |
| Signal System | PAL/NTSC | |
| Video Standard | AHD/TVI/CVI/CVBS standard | |
| Video Output | 1CH AHD/TVI/CVI/CVBS standard Standard Singal Output(Switchable) | |
| Max Transmission Distance | Common 75-3 cables can be up to 500m | |
| Lens and IR | | |
| Lens | 2,8-12mm manual iris lens | |
| IR distance | 42pcs F5 ir led , 40m night vision distance | |
| Function | | |
| Shutter Speed | 4/25s-1/45,000s | |
| BLC | Off/Low/Medium/High/Highest | |
| White Balance | Auto White Balance | |
| HLC | Support | |
| Operation Temperature | -10°C~55°C | |
| Power Supply | DC12V | |