



- * Using the high performance sensor, image is clear and delicate;
- * Support IR-CUT dual filter switch, to achieve day and night monitoring, color is not partial and distortion;
- * AHD/TVI/CVI/1200TVL 4 in 1 video output;
- * can access to many brands HD DVR;
- * Support the ultra low illumination;
- * Support automatic electronic shutter function, adapt to different monitoring environment;
- * 30pcs F5 ir led, 30m ir distance, DC12V
- * Metal, Waterproof IP66

Specification

Product Name	CCTV 4X/5X Zoom 2.0MP HD Video Security Surveillance IR Dome Camera		
Model No.	WDM-C6136UZ	WDM-C6136PZ	WDM-C6136KZ
Video			
Sensor	NVP2440H+Sony IMX323	NVP2441H+Sony IMX291	NVP2450H+IMX290
Output resolution	2.0MP (1920*1080)		
D/N Mode	IR cut Auto switching		
WDR	-	-	Support
DNR	2D DNR	3D DNR	3D DNR
Minimum Illumination	0.000LUX/F1.2(Led on)		
Effective Pixel	PAL: (1920*1080)@25fps		
	NTSC: (1920*1080)@30fps		
Signal System	PAL/NTSC		
Video Standard	AHD/TVI/CVI/CVBS standard		
Video Output	1CH AHD/TVI/CVI/CVBS standard Standard Singal Output(Switchable)		
Max Transmission Distance	Common 75-3 cables can be up to 500m		
Lens and IR			
Lens	4X Zoom(2.8-12mm auto iris lens)/5X Zoom(2.7-13.5mm auto irs)		
IR distance	30pcs F5 ir led, 30m ir distance		
Function			
Shutter Speed	4/25s-1/45,000s		
BLC	Off/Low/Medium/High/Highest		
White Balance	Auto White Balance		
HLC	Support		
Operation Temperature	-10°C~55°C		
Power Supply	DC12V		