



HD CCTV Total Solution
www.wardmay.com

Combinable HD-Cvi/Tvi/Ahd Passive CCTV UTP BNC Video Balun



WDM-UTP602AV

Specifications

Model | WDM-UTP602AV

Transmission distance

CVBS | 1200TVL / 500M

HD-AHD | 720P / 500M, 1080P / 300M

HD-TVI | 720P / 450M, 1080P / 2 80M

HD-CVI | 720P / 500M, 1080P / 300M

Features

- * Compatible with all HD-CVI, HD-TVI, HD-AHD Cameras and analog Cameras
- * No power required
- * 60dB cross talk and noise immunity
- * Compact size and easy installation
- * Built-in transient suppression protection
- * Innovative combinable design
- * Joining by screws video transfer

Technical specifications

Wire Type	UTP5
UTP Connection	"Press-Fit" terminal blocks
Video Format	HD-CVI/TVI/AHD, NTSC, PAL, and SECAM
Case	ABS Plastic
Frequency Response	DC to 60MHz
Attenuation	0.5dB typ
CMRR	60 dB
Surge protection	4KV
ESD	8KV
Power	No power required
Working Temperature	-10°C to +50°C
Storage Temperature	-30°C to +70°C
Humidity	0 to 95%