

H.265 1.3/2.0/4.0MP CCTV Video Security Surveillance IR Dome IP Camera



Features

- *Hisilicon high-performance DSP
- *High quality progressive scanning CMOS
- *H.265 High profile
- *support dual stream, support mobile phone
- *support power supply DC12V/POE(optional)
- *Standard ONVIF Protocol
- *Complete SDK for second development. Support multi network protocols
- *Provide a unified free client to achieve video recording/playback/preview
- *Support ICR filter switching function, day and night surveillance
- * Metal case

Dimension



Accessories

- User Manual
- CD
- Screw fittings

Specification				
Product Name	H.265 1.3/2.0/4.0MP CCTV Video Security Surveillance IR Dome IP Camera			
Model No.	WDM-IP8723R	WDM-IP8723S	WDM-IP9723D	
Video				
System	Hisilicon high-performance DSP, Hi3518C+AR0130	Hisilicon high-performance DSP, Hi3516C+IMX322	Hisilicon high-performance DSP, Hi3516D+OV4689	
Sensor	1.3M Pixel 1/3" CMOS Sensor	2.0M Pixel 1/3" CMOS Sensor	4.0M Pixel 1/3" CMOS Sensor	
Output resolution	1280(H)×960(V)	1920(H)×1080(V)	2592(H)×1520(V)	
D/N Mode	Auto switching,black and white vide and IR cut action linkage			
Illumination	Color 1.0Lux@F1.2,Black 0.1 Lux@F1.2			
Video processing	H.265 video compression, dual streaming			
	AVI format, 0.1M~6Mbps adjustable;			
Video Output	Main streaming: 1280×960,1280×720,1024×768,1280×720; Sub streaming: 960×540,640×360,480×270,352×288,320×240,352×192,320×192,288×192,256×192	Main streaming: 1920×1080,1280×960,1280×720,1024×768,1280×720; Sub streaming: 960×540,640×360,480×270,352×288,320×240,352×192,320×192,288×192,256×192	Main streaming: 2592×1520,1920×1080,1280×960,1280×720,1024×768,1280×720; Sub streaming: 960×540,640×360,480×270,352×288,320×240,352×192,320×192,288×192,256×192	
	Frame rate	1.3MP 25/30 frame(full real time),support 1~30frame/seconds adjustable	2.0MP 25/30 frame(full real time),support 1~30frame/seconds adjustable	4.0MP 25/30 frame(full real time),support 1~30frame/seconds adjustable
	Network interface	RJ45 ethernet,10/100M;RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP protocol supported		
Access Protocol	Standard ONVIF Protocol, Support third party access; PC;			
	Support IE6.0 and aboveSmartphone			
	Support Android/iPhone			
Lens				
Lens	2.8-12mm manual lens			
IR distance	30m(30pcs f5 IR leds)			
Function				
Function	Support WEB configuration, OSD,real-time video transmission			
	Support motion detection			
	Support front end storage ,playback and download			
	Support uniform client and platform system application			
Support complete SDK for second development.				
Normal				
Power supply	DC12V/POE(optional)			
Operation temperature	-10°C~+60°C,10%~90%RH			