



- \* Support 4ch 5.0MP/4chs 4.0MP video access/Support 2chs 5.0MP/4chs 4.0MP/16chs 960P access
- \* POE Ethernet power supply; 4/8 standard POE ports
- \* H.265
- \* Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc
- \* Support ONVIF Protocol; support GB28181 Protocol (Optional)
- \* Support WEB, CMS, VMS, MYEYE Platform, provide SDK for develop
- \* Support Mobile Phone Monitoring (IOS, Android)
- \* Cloud Services, P2P, Alarm Information Push To Phone
- \* Support Multi-Language
- \* Support Multi-browser access (IE, Chrome, Firefox, Safari)

## Specifications

Product Name	<b>4/8ch H.265 Network Poe NVR</b>	
Model No.	WDM-NVR8804T1MD-POE	WDM-NVR8808T1MD-POE

## System

Operating System	Embedded linux
------------------	----------------

## Video

Video compression	H.265+ / H.265 / H.264	
Video Input	4ch 5.0MP / 4chs 4.0MP	2chs 5.0MP / 4chs 4.0MP / 16chs 960P
Playback	2ch 5.0MP / 4chs 4.0MP	2ch 5.0MP / 4chs 4.0MP / 16chs 960P

## Audio

Audio compression	G.711A
Voice intercom	Nonsupport

## Management

Record mode	Manual > Alarm > Motion detection > Timing
Inquire mode	Inquire by Time / Calendar / Event / Channel
Storage mode	HDD Storage, Network Storage
Backup	Network, USB, SATA

## Interface

HDMI output	1*HDMI (MAX: 5.0MP)	
VGA output	1*VGA (MAX: 1080P)	
Ethernet	1*10/100Mbps Ethernet port, RJ45 port	
Poe	4*standard POE ports	8*standard POE ports
Audio In/Out	0/1	0/1
Alarm In/Out	0/0	
USB	2*USB2.0 ports	
HDD	1*SATA interface (Up to 8TB)	

## General

Power supply	48V/1.5A	48V/2.5A
Consumption	<10W (Without HDD)	
Working temperature	0 °C - + 55 °C	
Working humidity	10% - 90% RH	