



- \* Using the high performance sensor, image is clear and delicate;
- \* Support IR-CUT dual filter switch, to achieve day and night monitoring, color is not partial and distortion;
- \* AHD/TVI/CVI/1200TVL 4 in 1 video output;
- \* can access to many brands HD DVR;
- \* Support the ultra low illumination;
- \* Support automatic electronic shutter function, adapt to different monitoring environment;
- \* 30m night vision distance, 36pcs F5 ir led , DC12V
- \* Metal, Waterproof IP65

### Specification

Product Name	CCTV 2.0MP IR Dome HD Video Security Surveillance AHD Camera					
Model No.	WDM-AHD6361G	WDM-AHD6361S	WDM-AHD6361U	WDM-AHD6361H	WDM-AHD6361P	WDM-AHD6361K
<b>Video</b>						
Sensor	XM330+2235	FH8536+AR0232	V30E+Sony IMX323	NVP2441H+Sony IMX322	NVP2441H+Sony IMX291	FH8550M+Sony IMX290
Output resolution	2.0MP (1920*1080)					
D/N Mode	IR cut Auto switching					
WDR	-	-	-	-	-	Support
DNR	2D DNR	2D DNR	2D DNR	3D DNR	3D DNR	3D DNR
Minimum Illumination	0.000LUX/F1.2(Led on)					
Effective Pixel	PAL: (1920*1080)@25fps					
	NTSC: (1920*1080)@30fps					
Signal System	PAL/NTSC					
Video Standard	AHD/TVI/CVI/CVBS standard					
Video Output	1CH AHD/TVI/CVI/CVBS standard Standard Singal Output(Switchable)					
Max Transmission Distance	Common 75-3 cables can be up to 500m					
<b>Lens and IR</b>						
Lens	2.8-12mm manual iris lens					
IR distance	30m night vision distance, 36pcs F5 ir led					
<b>Function</b>						
Shutter Speed	4/25s-1/45,000s					
BLC	Off/Low/Medium/High/Highest					
White Balance	Auto White Balance					
HLC	Support					
Operation Temperature	-10°C~55°C					
Power Supply	DC12V					