

HD CCTV 1000TVL Super Mini Pinhole CCD MDVR Camera



Features

1. MDVR Camera
2. HD low illuminance 1/3" Mini CCTV camera (with shell and audio)
3. System standard: NTSC/ PAL
4. Support IR-CUT dual filter switch, to achieve day and night monitoring, color is not partial and distortion
5. Analog HD 1000TVL AHD video output
6. Support automatic electronic shutter function, adapt to different monitoring environment
7. DC 3.3V-6V

Accessories

- User Manual
- Warranty Card
- Screw fittings
- Desiccant

Specifications

Model	WDM-MD6405C
Camera	
Sensor	1/3" CMOS CCD
System	PAL/NTSC
Resolution	1000TVL
Lens&vision	0.5mm F1.2 / 55°
Video	
Pixels	PAL: 786(H)×576(V) / NTSC: 656(H)×492(V)
Scanning	2:1 Interlace
Sync Mode	Internal
Horizontal/vertical Frequency	PAL: 15.625 kHz, 50.00 HZ / NTSC : 15.734kHz, 59.94HZ
Video Output	1.0Vp-p/75Ω Composite video signal
S/N Ratio	>≥52dB (AGC off)
D/N	Dual filter switching (IR CUT)
Illumination	0.008Lux /F1.2
Features	
OSD Support	Yes, cable with OSD
Menu Language	EN, CN, DE, FRA, IT, ES, PL, RU, PT, NL, TR...
White Balance	AUTO / MANUAL
Picture Adjustment	Yes
Normal	
Power	DC 3.3V-6V
Operating Temperature	-10°C-50°C
Dimension	11.5mm x 11.5mm x 17mm