



- \* Using the high performance sensor, image is clear and delicate;
- \* Support IR-CUT dual filter switch, to achieve day and night monitoring, color is not partial and distortion;
- \* AHD/TVI/CVI/1200TVL 4 in 1 video output;
- \* can access to many brands HD DVR;
- \* Support the ultra low illumination;
- \* Support automatic electronic shutter function, adapt to different monitoring environment;
- \* 42pcs F5 ir led, 40m ir distance, DC12V
- \* Metal, Waterproof IP66

### Specification

|                           |   |
|---------------------------|---|
| Product Name              | <b>CCTV 4.0MP HD Video Security Surveillance IR Bullet AHD Camera</b> |
| Model No.                 | WDM-AHD6213W  |
| <b>Video</b>              |   |
| Sensor                    | NVP2475H+OV4689   |
| Output resolution         | 4.0MP(2592x1520)  |
| D/N Mode                  | IR cut Auto switching   |
| Minimum Illumination      | 0.000LUX/F1.2(Led on)   |
| Effective Pixel           | PAL: (2592x1520)@25fps  |
|                           | NTSC: (2592x1520)@30fps   |
| Signal System             | PAL/NTSC  |
| Video Standard            | AHD/TVI/CVI/CVBS standard   |
| Video Output              | 1CH AHD/TVI/CVI/CVBS standard Standard Singal Output(Switchable)      |
| Max Transmission Distance | Common 75-3 cables can be up to 500m                                  |
| <b>Lens and IR</b>        |   |
| Lens                      | 2,8-12mm manual iris lens   |
| IR distance               | 42pcs F5 ir led , 40m night vision distance                           |
| <b>Function</b>           |   |
| Shutter Speed             | 4/25s-1/45,000s   |
| BLC                       | Off/Low/Medium/High/Highest   |
| White Balance             | Auto White Balance  |
| HLC                       | Support   |
| Operation Temperature     | -10°C~55°C  |
| Power Supply              | DC12V   |