

**CCTV 4chs 2.0MP Security Surveillance Alarm DVR Systems**


- \* 1\*4chs HD Dvr,4chs video/network;
- \* 2\*outdoor 30m IR waterproof AHD cameras(metal case)
- \* 2\*indoor 30m IR Dome cameras(metal case)
- \* 4\*18.3m(60 feet) Video+power cable
- \* 1\* 12v2A Power supply with 1 to 4 DC cable
- \* Not included HDD

Model Number	WDM-LAHD04G-B	WDM-LAHD04U-B
--------------	---------------	---------------

**AHD Cameras specifications**
**Video**

Sensor	XM330+2235	FH8536H+Sony IMX323
Resolution	2.0MP (1920*1080)	
Minimum Illumination	0.000LUX/F1.2(Led on)	
Day/Night Mode	Color During day/switches to B&W at night	
Signal System	PAL/NTSC	
Effective Pixel	PAL: (1920*1080)@25fps; PAL: (1920*1080)@30fps	
Video Standard	AHD/TVI/CVI/1200TVL CVBS Standard	

**Lens and IR**

Lens	3.6mm
IR Distance	Up to 30m
IR Cut Filter	yes

**General**

Waterproof	IP66
Indoor / Outdoor	Suitable for Indoor or Outdoor use
Power Input	DC12V1A (4pcs)
Working Temperature	-10°C ~+60°C

**DVR Specifications**

Operating System	Embedded linux
------------------	----------------

**Video&Audio**

Video compression	H.264
Encode	4*AHD 1080P
Analog input	4*AHD 1080P
Hybrid input	2*AHD 1080P(analog)+2*1080P(Network)
Audio Input	4 RCA Input
Audio Output	1 RCA Output
Audio compression	G.711A

**Recording**

Compression Format	H.264
Recording Modes	Manual/Motion/Schedule
Hard drive	Internal SATA hard drive required for recording,support up to 4TB

**Network**

LAN Connection	YES
Network Interface	RJ45

**Interface**

Video input	4ch BNC
Video output	1ch VGA, 1ch HDMI
USB	2* USB 2.0
HDD	1*SATA port (Max 4TB/per)

**General**

Power Supply	DC 12V
Back up method	External storage via USB
Temperature/Humidity	-20°C+50°C; -10%-90%
Remote Control	YES

**DVR Language**

Russian, English, Finnish, French, German, Greek, Italian, Japanese, Poland, Portugal, Spanish, Thai, Turkey Romanian, Slovakia, Czech, Arabic, Swedish and so on