



| JSP-5MP New CCTV Bulker IP Camera | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|---|--|------------------|------------|--------------|--|---------------|---|--------------------------|---|----------------|--|---------------------|-------------------------------------|-------------------------|--|-------------------|--|--------------------------|--|------------------------|---|------------------------|------------------------------------|--------------|-------------------------|-------------|------------------|--------------------|--------------------------|-----------------|---|-----------------|--------------------------|--|--|--|--|--|---|---------------|--|---------------------|---------------------|--------------|---------|-------------|----------|-------------------|----------|-----------|----------|---------------|----------|------------------|-----------------------|
|  | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Features</p> <ul style="list-style-type: none"> • Highest high-performance CMOS • High quality progressive scanning CMOS • H.265 High-profile • Standard ONVIF Protocol • Complete SDK for second development. Support multi network protocol. • Provide a unified free client to achieve video recording/playback/network. • Support ICR filter switching function, day and night surveillance. <p>Dimension</p>  | <p>Specification</p> <table border="1"> <tr> <td colspan="2">Product Name JSP-5MP New CCTV Bulker IP Camera</td> </tr> <tr> <td>Model No.</td> <td>JSP-5MP-12</td> </tr> <tr> <td colspan="2">Video</td> </tr> <tr> <td>Format</td> <td>H.265 + H.264/1080P/720P/960P/540P/480P/360P/300P/270P/240P/200P/180P/160P/144P/128P/120P/96P/72P/64P/48P/36P/30P/24P/20P/16P/12P/8P/6P/4P/3P/2P/1P</td> </tr> <tr> <td>Output resolution</td> <td>1080P/960P/720P/540P/480P/360P/300P/270P/240P/200P/180P/160P/144P/128P/120P/96P/72P/64P/48P/36P/30P/24P/20P/16P/12P/8P/6P/4P/3P/2P/1P</td> </tr> <tr> <td>3D Mode</td> <td>Auto switching black and white video and IR cut action linkage</td> </tr> <tr> <td>Illumination</td> <td>Color 1 Lux@F1.2,Black 0.1 Lux@F1.2</td> </tr> <tr> <td>Video processing</td> <td>4:2:0 video compression, Lossless coding</td> </tr> <tr> <td>Frame rate</td> <td>25MP/20 frame/s(ultra real time),support 1~200 frame/s(adjustable)</td> </tr> <tr> <td>Network interface</td> <td>Support Ethernet 10/100M/RTSP/HTTP/PPPOE/DHCP/IGMP/NDP/SNMP protocol supported</td> </tr> <tr> <td>Access Protocol</td> <td>Standard ONVIF Protocol. Support third party access: P2P.</td> </tr> <tr> <td>Access Protocol</td> <td>Support RS-485 and alarm telephone</td> </tr> <tr> <td>Alarm</td> <td>Support Alarm telephone</td> </tr> <tr> <td>Lens</td> <td>3.6mm Fixed lens</td> </tr> <tr> <td>IR distance</td> <td>30M, 50M, 60M, 80M, 100M</td> </tr> <tr> <td>Material</td> <td>Support WEB configuration, OSD real-time video transmission</td> </tr> <tr> <td>Function</td> <td>Support motion detection</td> </tr> <tr> <td></td> <td>Support front end storage, playback and download</td> </tr> <tr> <td></td> <td>Support uniform client and platform system application</td> </tr> <tr> <td></td> <td>Support complete SDK for second development</td> </tr> <tr> <td colspan="2">Remark</td> </tr> <tr> <td>Power supply</td> <td>DC 12V/1A(Optional)</td> </tr> <tr> <td>Audio</td> <td>Support</td> </tr> <tr> <td>WIFI</td> <td>Optional</td> </tr> <tr> <td>Smart Lens</td> <td>Optional</td> </tr> <tr> <td>IC</td> <td>Optional</td> </tr> <tr> <td>SD/SSD</td> <td>Optional</td> </tr> <tr> <td>Operation</td> <td>-10°C~60°C, 10%~90%RH</td> </tr> </table> | Product Name JSP-5MP New CCTV Bulker IP Camera | | Model No. | JSP-5MP-12 | Video | | Format | H.265 + H.264/1080P/720P/960P/540P/480P/360P/300P/270P/240P/200P/180P/160P/144P/128P/120P/96P/72P/64P/48P/36P/30P/24P/20P/16P/12P/8P/6P/4P/3P/2P/1P | Output resolution | 1080P/960P/720P/540P/480P/360P/300P/270P/240P/200P/180P/160P/144P/128P/120P/96P/72P/64P/48P/36P/30P/24P/20P/16P/12P/8P/6P/4P/3P/2P/1P | 3D Mode | Auto switching black and white video and IR cut action linkage | Illumination | Color 1 Lux@F1.2,Black 0.1 Lux@F1.2 | Video processing | 4:2:0 video compression, Lossless coding | Frame rate | 25MP/20 frame/s(ultra real time),support 1~200 frame/s(adjustable) | Network interface | Support Ethernet 10/100M/RTSP/HTTP/PPPOE/DHCP/IGMP/NDP/SNMP protocol supported | Access Protocol | Standard ONVIF Protocol. Support third party access: P2P. | Access Protocol | Support RS-485 and alarm telephone | Alarm | Support Alarm telephone | Lens | 3.6mm Fixed lens | IR distance | 30M, 50M, 60M, 80M, 100M | Material | Support WEB configuration, OSD real-time video transmission | Function | Support motion detection | | Support front end storage, playback and download | | Support uniform client and platform system application | | Support complete SDK for second development | Remark | | Power supply | DC 12V/1A(Optional) | Audio | Support | WIFI | Optional | Smart Lens | Optional | IC | Optional | SD/SSD | Optional | Operation | -10°C~60°C, 10%~90%RH |
| Product Name JSP-5MP New CCTV Bulker IP Camera | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Model No. | JSP-5MP-12 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Video | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Format | H.265 + H.264/1080P/720P/960P/540P/480P/360P/300P/270P/240P/200P/180P/160P/144P/128P/120P/96P/72P/64P/48P/36P/30P/24P/20P/16P/12P/8P/6P/4P/3P/2P/1P | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Output resolution | 1080P/960P/720P/540P/480P/360P/300P/270P/240P/200P/180P/160P/144P/128P/120P/96P/72P/64P/48P/36P/30P/24P/20P/16P/12P/8P/6P/4P/3P/2P/1P | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3D Mode | Auto switching black and white video and IR cut action linkage | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Illumination | Color 1 Lux@F1.2,Black 0.1 Lux@F1.2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Video processing | 4:2:0 video compression, Lossless coding | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Frame rate | 25MP/20 frame/s(ultra real time),support 1~200 frame/s(adjustable) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Network interface | Support Ethernet 10/100M/RTSP/HTTP/PPPOE/DHCP/IGMP/NDP/SNMP protocol supported | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Access Protocol | Standard ONVIF Protocol. Support third party access: P2P. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Access Protocol | Support RS-485 and alarm telephone | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Alarm | Support Alarm telephone | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Lens | 3.6mm Fixed lens | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| IR distance | 30M, 50M, 60M, 80M, 100M | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Material | Support WEB configuration, OSD real-time video transmission | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Function | Support motion detection | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | Support front end storage, playback and download | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | Support uniform client and platform system application | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | Support complete SDK for second development | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Power supply | DC 12V/1A(Optional) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Audio | Support | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WIFI | Optional | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Smart Lens | Optional | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| IC | Optional | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| SD/SSD | Optional | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Operation | -10°C~60°C, 10%~90%RH | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |