CCTV 4.0MP IR HD Mini Video Surveillance AHD Camera



Features

- 1,Using the high performance sensor, image is
- clear and delicate;
- 2,Support IR-CUT dual filter switch, to achieve day and night monitoring, color is not partial anddistortion;
- 3,Analog HD 4.0MP AHD video output;
- 4, Support the ultra low illumination;
- 5,Support automatic electronic shutter function, adapt to different monitoring environment;
- 6, 3.6/6mm screw/pinhole lens , DC12V
- 7, black/silver; 40*40*12mm; 100g

Accessories

User Manual Warranty Card

Screw fittings

Desiccant

| Specification | |
|---------------------------|--|
| | |
| Model No. | WDM-AHD6420W |
| Video | |
| Sensor | (8538+OV4603) |
| Output resolution | 4.0MP (2592×1520) |
| D/N Mode | IR cut Auto switching |
| Minimum Illumination | 0.000LUX/F1.2(Led on) |
| Effective Pixel | PAL: (2592*1520)@25fps |
| | NTSC: (2592*1520)@30fps |
| Signal System | PAL/NTSC |
| Video Standard | AHD/TVI/CVI/CVBS standard |
| Video Output | 1CH AHD/TVI/CVI/CVBS standard Standard Singal Output(Switchable) |
| Max Transmission Distance | Common 75-3 cables can be up to 500m |
| Lens and IR | _ |
| Lens | 3.6/6mm screw/pinhole lens |
| Function | |
| OSD | Support |
| Shutter Speed | 4/25s-1/45,000s |
| BLC | Off/Low/Medium/High/Highest |
| White Balance | Auto White Balance |
| HLC | Support |
| Operation Temperature | -10°C~55°C |
| Power Supply | DC12V |