



- \* Support 36chs 4K Video access storage
- \* Support H.265+/H.265/H.264, support iS super protocol, plug and play.
- \* Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc
- \* Support ONVIF Protocol; support GB28181 Protocol (Optional)
- \* Support WEB, CMS, VMS, MYEYE Platform, provide SDK for develop
- \* Support Mobile Phone Monitoring (IOS, Android)
- \* Cloud Services, P2P, Alarm Information Push To Phone
- \* supports max 8channels intelligent analysis locally (target counting, item detection, area detection, virtual warning line)

## Specifications

Product Name	<b>Wdm Security 1.5U H.265 36chs 4K Network Security NVR</b>
Model No.	WDM-NVR88364MD

## Video and Audio

Network video input	36chs network compressed video input(4K compatible with resolution below 4K)
Access bandwidth	300M
Audio input	IPC compound audio input
HDMI/Output	1*HDMI, 1*VGA, Resolution: 3840×2160/30Hz, 1920×1080/60Hz, 1280X1024/60Hz
Audio output	1*RCA
Video compression	H.265+/H.265/H.264 /MJPEG
Resolution	12M/8M/5M/3M/1080P/720P
Playback	4*4K; 9*4MP; 16*1080P

## Management

Record/Screenshot mode	Manual>Timing>Event>Motion detection>Alarm>Motion detect or Alarm>Motion detect and Alarm
Playbck mode	Instant playback, regular playback, event playback, external file playback, log playback
Storage mode	HDD Storage, Network Storage
Backup	General backup, event backup, Video clip backup

## Interface

Ethernet	1*10/100Mbps Ethernet port, RJ45 port
serial interface	Full duplex standard RS-485 interface
Alarm In/Out	4/1
Audio In/Out	1/1
USB	3*USB, 1 USB2.0 interface front, 1 USB2.0+1 USB3.0 interface post
HDD	4*SATA interface+1*E-SATA(Up to 8TB)

## Network

Networking protocol	ONVIF, IPv4, UPnP, NTP, SADP, PPoE, DHCP, etc
---------------------	---

## General

Power supply	12V6A
Consumption	<25W (Without HDD)
Working temperature	0 °C - + 55 °C
Working humidity	10% -90% RH
Chassis	NVR: 440mmx356mmx68.5mm Package: 555mmx450mmx130mm
Weight(without HDD)	Net weight: 5.7 kg; package: 6.9kg