

4.5" 20X/33X 2.0MP Video Surveillance IR High Speed Dome PTZ AHD Camera



Features

- * 4.5" High speed dome camera ,IP66 rate protection
- * 1/3" 2.0M Pixel Sony CMOS
- * High definition 1080P,4X/10X Zoom
- * OSD menu available, IR Range:150m
- * Long distance transmission up to 500 meters over coax cable
- * Real time transmission ,lossless video
- * Pan/Tilt/Zoom, A-B scan, tour available

Dimension



Accessories

- Instruction book
- Warrant card
- Screw fittings
- Desiccant

Specifications

Product Name	20X/33X 2.0MP Video Surveillance IR High Speed Dome PTZ AHD Camera		
Model NO.	WDM-AHD8886FMX -20X	WDM-AHD8886FMX -S-20X	WDM-AHD8886FMX -33X
Camera			
Image Sensor	1/3" 2.0M pixels CMOS Nextchip 2441+Sensor Sony 323	1/3" 2.0M pixels CMOS Nextchip 2441+Sensor Sony 307	1/3" 2.0M pixels CMOS Nextchip 2441+Sensor Sony 323
Lens	lens 20X Zoom f=4.7mm ~ 94mm	lens 20X Zoom f=4.7mm ~ 94mm	lens 33X Zoom f=4.6mm ~ 165mm
Image Resolution	HD:1080p/30fps /1080p/25fps		
Effective Pixels	2.0MP(1920x1080)		
TV System	PAL/NTSC		
Electronic Shutter	AUTO/ 1/50 (1/60)-1/100,000sec		
Min.illumination	0.05lux (color), 0.005lux (B/W), 0lux (IR)		
S/N Rate	>=50db		
White Balance	Auto		
IR-Cut	Auto		
IR Control	PWM		
IR Range	150m		
Dome			
Horizontal Rotation Range	360°		
Title Rotation Range	90°		
Pan speed	200°/sec		
Tilt Speed	100°/sec		
Ratio Speed	Support		
Preset Points	220		
Guard Tours	3 Groups		
Guard Points	Max.16 points		
OSD Menu	Multiple languages for OSD Menu		
Park time	1-60mins setting available		
Baud Rate	1200/2400/4800/9600bps		
Video Output	AHD/CVI/TVI/CVBS selectable		
Communication mode	UTC&RS485 Coaxial cable		
General			
Certification	CE, FCC, RoHS, IP66		
Operating Temperature	-20℃ - +60℃		
Operating Humidity	<=95%		
Power supply	DC12V4A		
Lightning Protection	Transient voltage 6000V		