



- \* Support 8ch 8MP/16ch 4MP unreal-time encoding
- \* Support Xvi,AHD, TVI,CVI, CVBS, IP video input
- \* Support VGA maximum 1080P output, HDMI up to 4K output
- \* Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc
- \* Support the Onvif protocol
- \* Support WEB, CMS, VMS, MYEYE Platform
- \* Mobile phone remote monitoring (iOS, Android)
- \* Cloud services, P2P, alarm information push to phone
- \* Support for more than twenty languages

## Specifications

Product Name	8/16chs 6 In 1 Network AHD DVR	
Model No.	WDM-DVR6508DA-GL	WDM-DVR6516DA-GS

## System

Processor	Hi3531D	Hi3531D
-----------	---------	---------

## Video

Video compression	H.265+	
Encode	8*8M@8fps(AHD); 8*5M@14fps(6 in 1); 8*4M@18fps(6 in 1); 8*3M@21fps (6 in 1); 8*1080P(6 in 1)	16*5M@6fps(6 in 1); 16*4M@8fps(6 in 1); 16*3M@10fps(6 in 1); 16*1080P@12fps(6 in 1); 16*720P(6 in 1)
Decode	8*8M@6fps(AHD); 8*5M@8fps(6 in 1); 8*4M@8fps(6 in 1); 8*3M@8fps (6 in 1); 8*1080P(6 in 1)	16*5M@6fps(6 in 1); 16*4M@8fps(6 in 1); 16*3M@10fps(6 in 1); 16*1080P@12fps(6 in 1); 16*720P(6 in 1)
Multi-mode	Analog:8*8M; 8*5M	Analog:16*4M; 16*1080P
	Hybird:4*5M@20fps(analog) +4 *5M(network)	Hybird:8*4M@6fps(analog) + 8*4M (network)
	IP: 8*3M; 4*5M	IP: 8*3M ;4*5M
Playback	8ch	16ch

## Audio

Audio compression	G.711A
-------------------	--------

## Management

Record mode	Manual>Alarm>Motion detection>Timing
Inquire mode	Inquire by Time/Calendar/Event/Channel
Storage mode	HDD Storage, Network Storage
Backup	Network, USB, SATA

## Interface

Video Input	8*BNC (Support Coaxitron)	16*BNC (Support Coaxitron)
HDMI output	1*HDMI (MAX:4K)	1*HDMI (MAX: 5.0MP)
VGA output	1*VGA (MAX:1080P)	
Audio In/Out	4/1	4/1
Alarm In/Out	4/1	
Ethernet	1*10/100Mbps Ethernet port, RJ45 port	
PTZ Control	1*RS485, Support for multiple PTZ protocol	
USB	2*USB2.0 ports	
HDD	2*SATA interface (Up to 8TB)	

## General

Power supply	DC12V 4A
Consumption	<10W(Without HDD)
Working temperature	0℃--+55℃
Working humidity	10%--90%
Chassis	Mini 1 U