

## IHD CCTFV Total Solution

## www.wardmay.com



- \* Using the high performance sensor, image is clear and delicate;
- \* Support IR-CUT dual filter switch, to achieve day and night monitoring, color is not partial and distortion;
- \* AHD/TVI/CVI/1200TVL 4 in 1 video output;
- \* can access to many brands HD DVR;
- \* Support the ultra low illumination;
- \* Support automatic electronic shutter function, adapt to different monitoring environment;
- \* 40m night vision distance, 48pcs F5 ir led, DC12V
- \* ABS, Waterproof IP66

Specification	
Product Name	CCTV 2.0MP IR Dome HD Video Security Surveillance AHD Camera
Model No.	WDM-AHD6368G
Video	
Sensor	XM320+2235
Output resolution	2.0MP (1920*1080)
D/N Mode	IR cut Auto switching
WDR	-
DNR	2D DNR
Minimum Illumination	0.000LUX/F1.2(Led on)
Effective Pixel	PAL: (1920*1080)@25fps
	NTSC: (1920*1080)@30fps
Signal System	PAL/NTSC
Video Standard	AHD/TVI/CVIS standard
Video Output	1CH AHD/TVI/CVI/CVBS standard Standard Singal Output(Switchable)
Max Transmission Distance	Common 75-3 cables can be up to 500m
Lens and IR	
Lens	3.6mm fixed iris lens
IR distance	40m night vision distance, 48pcs F5 ir led
Function	
Shutter Speed	4/25s-1/45,000s
BLC	Off/Low/Medium/High/Highest
White Balance	Auto White Balance
HLC	Support
Operation Temperature	-10°C~55°C
Power Supply	DC12V