

4.5" CCTV HD Outdoor 2.0MP 36X High Speed Dome IP PTZ Camera



Features

- * 4.5" double layer metal body construction, IP66 rate protection
- * 1/3" CMOS, 2.0 Megapixels, 36X optical zoom
- * HD-IP digital interface output, 2.0MP high definition image
- * PWM function, intelligent IR illumination & power consumption is variable, dependant the zoom factor
- * IR distance 60M
- * Support P2P function, OSD menu is available
- * ONVIF2.4 compatible; good compatibility with NVRs like DAHUA , HIKVISION , JUFENG and AXXON , Milestone and so on

Dimension



Accessories

- Instruction book
- Warrant card
- Screw fittings
- Desiccant

| | |
|-------------------------|---|
| Product Name | 4.5" HD-IP IR High Speed dome 2.0MP 36X IP PTZ Camera |
| Camera | |
| Model Number | WDM-IP8854F-36X |
| Image Sensor | 1/3" 2.0M pixels CMOS Hi3516D+Sensor Panasonic 34229 |
| Effective Pixels | 2.0MP(1920x1080) |
| Min. Illumination | Color; 0.05Lux@(F1.6, AGC ON) ; 0.01Lux@(F1.6, AGC ON) |
| Zoom | 36X optical zoom, f=4.6-167mm, D/N(ICR-Cut) ,F1.6~F1.8 |
| Day/Night | Day / Night / External control (IR Cut Filter) |
| SNR | ≥50dB(AGC OFF) |
| WDR | Digital WDR≥70dB |
| AGC | Auto / Manual |
| White balance | Auto/Manual /ATW/Indoor/Outdoor/Daylight lamp/Sodium lamp |
| Digital noise Reduction | DNR, 3DNR |
| Network | |
| Video Compression | H.265/H.264 Main Profile/M-JPEG |
| Max Image Size | 1920X1080@30fps |
| Streams | Dual streams |
| Frame Rate | Main stream: 1920*1080, 1280*960, 1280*720,720*576, 640*480 Sub-stream: 640*480,480*360, 352*288, 320*240, 176*144 |
| Bitrate | CBR/VBR, bitrate; 32Kbps~10Mbps variable |
| Audio Compression | G711, PCM |
| P2P | Android / IOS |
| Protocols | TCP/IP,HTTP, NTP,IGMP, DHCP,UDP,SMTP,RTP,RTSP,ARP,DDNS,DNS,P2P |
| Motion detect | Support |
| Privacy Zone Masking | Support |
| Onvif | Onvif 2.4 |
| IR parameters | |
| Night vision distance | 60M |
| Dome Features | |
| Pan Range | 360° continued rotation |
| Tilt Range | 0~90°(Auto Flip) |
| Manual pan speed | 0.02~200°/S (1-64 degree variable) |
| Manual tilt speed | 0.02~120°/S (1-64 degree variable) |
| Actual preset Accuracy | ±0.10° |
| Preset points | 220 |
| Operation OSD language | Chinese /English |
| General | |
| Certification | RoHs ,CE,FCC,IP66 |
| Work temperature | External-35Celsius degree~65Celsius degree |
| Work Humidity | 0%~95% (Non condensing) |
| Temperature control | Intelligent control |
| Power | DC 12V |
| Consumption | ≤ 20W |
| Lightning Protection | Transient Voltage 6000V |