

HD CCTV 420/700/1000TVL Super Car Mini Pinhole CCD Camera



Features

- 1, Using the high performance sensor, image is clear and delicate;
- 2, Support IR-CUT dual filter switch, to achieve day and night monitoring, color is not partial and distortion;
- 3, Analog HD 420/700/1000TVL CCD video output;
- 4, Support the ultra low illumination;
- 5, Support automatic electronic shutter function, adapt to different monitoring environment;
- 6, Input power: DC12V
7. Mini, Φ 19mm/ Φ 16mm, with microphone

Accessories

- User Manual
- Warranty Card
- Screw fittings
- Desiccant

Specifications

Model	WDM-M6419C	WDM-M6419S	WDM-M6419G
Camera			
Sensor	1/4" CMOS CCD	1/3" Sony CCD	1/3" Sony CCD
System	PAL/NTSC		
Resolution	1000TVL	420TVL	700TVL
Lens	3.7mm Wide-angle Pinhole lens		
Video			
Effective Pixel	PAL:1368(H) \times 1049(V)	PAL:500(H) \times 582(V)	PAL: 976(H) \times 582(V)
	NTSC: 1368(H) \times 1049(V)	NTSC: 510(H) \times 492(V)	NTSC: 976(H) \times 494(V)
Scanning	2:1 Interlace		
Sync Mode	Internal		
Horizontal/vertical Frequency	PAL:15.625 kHz, 50.00 HZ / NTSC :15.734kHz,59.94HZ		
Video Output	1.0Vp-p/75 Ω Composite video signal		
S/N Ratio	\geq 52dB (AGC off)		
D/N	Dual filter switching (IR CUT)		
Illumination	0.00001Lux/F1.2 (color)		
Features			
OSD Support	Yes, cable with OSD		
Menu Language	EN, CN, DE, FRA, IT, ES, PL, RU, PT, NL, TR...		
White Balance	AUTO / MANUAL		
Picture Adjustment	Yes		
Normal			
Power	DC12V		
Operating Temperature	-10 $^{\circ}$ C-50 $^{\circ}$ C		
Dimension	Φ 19mm/ Φ 16mm		