

| * Support 16ch 1080N unreal-time encoding * Support XVI,AHD, TVI,CVI, CVBS, IP video input * Support VGA maximum 1080P output, HDMI up to 4K output * Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc * Support the Onvif protocol * Support WEB, CMS, VMS, MYEYE Platform * Mobile phone remote monitoring (iOS, Android) |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mobile phone remote monitoring (iOS, Android) Cloud services, P2P, alarm information push to phone Support for more than twenty languages |

Specifications

| • | | |
|---------------------|--------------------------------------------|--|
| Product Name | 16chs 1080N 6 In 1 Network AHD DVR | |
| Model No. | WDM-DVR6516A | |
| System | | |
| Processor | Hi3521D | |
| Video | | |
| Video compression | H.264 | |
| Encode | 16*1080N@15fps(6 in 1) | |
| Decode | 16*1080N@15fps(6 in 1) | |
| Multi-mode | Analog: 16*1080N@15fps(6 in 1) | |
| | Hybird: 8*1080P+8*960P; 4*5MP | |
| | IP: 8*1080N(analog)+8*960P(network) | |
| Playback | 16ch | |
| Audio | | |
| Audio compression | G.711a | |
| Intercom | Support | |
| Management | | |
| Record mode | Manual>Alarm>Motion detection>Timing | |
| Inquire mode | Inquire by Time/Calendar/Event/Channel | |
| Storage mode | HDD Storage, Network Storage | |
| Backup | Network, USB, SATA | |
| Interface | | |
| Video Input | 16*BNC (Support Coaxitron) | |
| HDMI output | 1*HDMI (MAX:1080P) | |
| VGA output | 1*VGA (MAX:1080P) | |
| Audio In/Out | 2/1 | |
| Alarm In/Out | 0/0 | |
| Ethernet | 1*10/100Mbps Ethernet port, RJ45 port | |
| PTZ Control | 1*RS485, Support for multiple PTZ protocol | |
| USB | 2*USB2.0 ports | |
| HDD | 1*SATA interface (Up to 8TB) | |
| General | | |
| Power supply | 12V/2A | |
| Consumption | <10W (Without HDD) | |
| Working temperature | 0 °C - + 55 °C | |
| Working humidity | 10% -90% RH | |
| Chassis | Mini 1U | |