

**HD-AHD 1.3/2.0MP Super Mini Bullet Pinhole Camera**



**Features**

- 1, Using the high performance sensor, image is clear and delicate;
- 2, Support IR-CUT dual filter switch, to achieve day and night monitoring, color is not partial and distortion;
- 3, Analog HD 1.3/2.0MP AHD video output;
- 4, Support the ultra low illumination;
- 5, Support automatic electronic shutter function, adapt to different monitoring environment;
- 6, DC12V
- 7, Iack; Φ20mm

**Accessories**

- User Manual
- Warranty Card
- Screw fittings
- Desiccant

**Specification**

Product Name	HD-AHD 1.3/2.0MP Super Mini Bullet Pinhole Camera	
Model No.	WDM-BT6420B	WDM-BT6420H
<b>Video</b>		
Output resolution	1.3MP(1280x960)	2.0MP(1920x1080)
D/N Mode	IR cut Auto switching	
Minimum Illumination	0.000LUX/F1.2(Led on)	
Effective Pixel	PAL : 1280*960@25fps	PAL : 1920*1080@25fps
	NTSC : 1280*960@25fps	NTSC : 1920*1080@25fps
Signal System	PAL/NTSC	
Video Standard	AHD and CVBS Standard	
Video Output	1CH AHD HD/CVBS Standard Singal Output(Switchable)	
Max Transmission Distance	Common 75-3 cables can be up to 500m	
<b>Lens and IR</b>		
Lens	3.7mm Wide-angle cone lens/Button/Screw camera lens.	
IR distance	not support	
<b>Function</b>		
Shutter Speed	4/25s-1/45,000s	
BLC	Off/Low/Medium/High/Highest	
White Balance	Auto White Balance	
HLC	Support	
Operation Temperature	-10°C~55°C	
Power Supply	DC12V	
Dimension	black; Φ20mm	