

HD CCTV 1000TVL Super Car Mini Pinhole CCD Camera



Features

- 1, Using the high performance sensor, image is clear and delicate;
- 2, Support IR-CUT dual filter switch, to achieve day and night monitoring, color is not partial and distortion;
- 3, Analog HD 1000TVL CCD video output;
- 4, Support the ultra low illumination;
- 5, Support automatic electronic shutter function, adapt to different monitoring environment;
- 6, Input power: 5V-12V
7. 4pin aviation connector

Accessories

- User Manual
- Warranty Card
- Screw fittings
- Desiccant

Specifications

Model	WDM-CZ64HDC
Camera	
Sensor	1/4" CMOS CCD
System	PAL/NTSC
Resolution	1000TVL
Lens	2.8mm
Video	
Pixels	PAL:1368(H)×1049(V) / NTSC: 1368(H)×1049(V)
Scanning	2:1 Interlace
Sync Mode	Internal
Horizontal/vertical Frequency	PAL:15.625 kHz, 50.00 HZ / NTSC :15.734kHz,59.94HZ
Video Output	1.0Vp-p/75Ω Composite video signal
S/N Ratio	>≥52dB (AGC off)
D/N	Dual filter switching (IR CUT)
Illumination	0.00001Lux/F1.2 (color)
Features	
OSD Support	Yes, cable with OSD
Menu Language	EN, CN, DE, FRA, IT, ES, PL, RU, PT, NL, TR...
White Balance	AUTO / MANUAL
Picture Adjustment	Yes
Normal	
Power	5V-12V
Operating Temperature	-10°C-50°C
Dimension	Φ23mm