



**Combinable HD-Cvi/Tvi/Ahd Passive CCTV UTP BNC Video Balun**

 <p>CE FC</p>		 <p>CE FC</p>	<b>Specifications</b>	
<b>WDM-UTP602A</b>		<b>WDM-UTP602K</b>	Model	WDM-UTP602A/K
<div style="background-color: #ff4500; color: white; padding: 5px; border-radius: 10px; display: inline-block;"><b>Features</b></div> <ul style="list-style-type: none"> <li>* Compatible with all HD-CVI, HD-TVI, HD-AHD Cameras and analog Cameras</li> <li>* No power required</li> <li>* 60dB cross talk and noise immunity</li> <li>* Compact size and easy installation</li> <li>* Built-in transient suppression protection</li> <li>* Innovative combinable design</li> <li>* Joining by screws video transfer</li> </ul>			<b>Transmission distance</b>	
			CVBS	720P/300M, 1080P/200M
			HD-AHD	720P/270M, 1080P/120M
			HD-TVI	720P/300M, 1080P/200M
			HD-CVI	720P/270M, 1080P/120M
			<b>Technical specifications</b>	
			Wire Type	UTP5
			UTP Connection	"Press-Fit" terminal blocks
			Video Format	HD-CVI/TVI/AHD, NTSC, PAL, and SECAM
			Case	ABS Plastic
			Frequency Response	DC to 60MHz
			Attenuation	0.5dB typ
			CMRR	60 dB
			Surge protection	4KV
			ESD	8KV
			Power	No power required
			Working Temperature	-10°C to +50°C
Storage Temperature	-30°C to +70°C			
Humidity	0 to 95%			