

法德镁 IHD CCTFV Total Solution

www.wardmay.com



- * Using the high performance sensor, image is clear and delicate;
- * Support IR-CUT dual filter switch, to achieve day and night monitoring, color is not partial anddistortion;
- * AHD/TVI/CVI/1200TVL 4 in 1 video output;
- * can access to many brands HD DVR;
- * Support the ultra low illumination;
- * Support automatic electronic shutter function, adapt to different monitoring environment;
- * 36pcs F5 ir led, 30m ir distance, DC12V
- * Metal, Waterproof IP66

Specification

| Product Name | CCTV 2.0MP HD Video Security Surveillance IR Bullet AHD Camera |
|------------------------------|------------------------------------------------------------------|
| Model No. | WDM-AHD6237K |
| Video | |
| Sensor | FH8550M+Sony IMX290 |
| Output resolution | 2.0MP (1920*1080) |
| D/N Mode | IR cut Auto switching |
| WDR | Support |
| DNR | 3D DNR |
| Minimum Illumination | 0.0001LUX/F1.2(Led on) |
| Effective Pixel | PAL: (1920*1080)@25fps |
| | NTSC: (1920*1080)@30fps |
| Signal System | PAL/NTSC |
| Video Standard | AHD/TVI/CVI/CVBS standard |
| Video Output | 1CH AHD/TVI/CVI/CVBS standard Standard Singal Output(Switchable) |
| Max Transmission Distance | Common 75-3 cables can be up to 500m |
| Lens and IR | |
| Lens | 3.6mm fixed iris lens |
| IR distance | 36pcs F5 ir led , 30m ir |
| Function | |
| Shutter Speed | 4/25s-1/45,000s |
| BLC | Off/Low/Medium/High/Highest |
| White Balance | Auto White Balance |
| HLC | Support |
| Operation Temperature | -10°C~55°C |
| Power Supply | DC12V |
| 2 | |