HD CCTV Total Solution

www.wardmay.com

Combinable HD-Cvi/Tvi/Ahd Passive CCTV UTP BNC Video Balun

WDM-UTP602L

WDM-UTPCCTV602L

Features

* Compatible with all HD-CVI, HD-TVI, HD-AHD Cameras and analog Cameras
* No power required
* 60dB cross talk and noise immunity
* Compact size and easy installation
* Built-in transient suppression protection
*screw interface, small size, anti surge protection, anti-interference, noisereduction
* Joining by screws video transfer

Specifications	
Model	WDM-UTP602L/WDM-UTPCCTV602L
Transmission distance	
CVBS	1200TVL / 600M
HD-AHD	720P/600M, 1080P/450M
HD-TVI	720P/600M, 1080P/450M, 3.0WP/350M
HD-CVI	720P/600M, 1080P/450M
Technical specifications	
Wire Type	UTP5
UTP Connection	"Press-Fit" terminal blocks
Video Format	HD-CVI/TVI/AHD, NTSC, PAL, and SECAM
Case	ABS Plastic
Frequency Response	DC to 60MHz
Attenuation	0.5dB typ
CMRR	60 dB
Surge protection	4KV
ESD	8KV
Power	No power required
Working Temperature	-10ºC to +50ºC
Storage Temperature	-30ºC to +70ºC
Humidity	0 to 95%