

H.265 5.0MP IR Dome CCTV Security Video Surveillance IP Camera



Features

- *Hisilicon high-performance DSP
- *High quality progressive scanning CMOS
- *H.265 High profile
- *support dual stream, support mobile phone
- *support power supply DC12V/POE
- *Standard ONVIF Protocol
- *Complete SDK for second development. Support multi network protocols
- *Provide a unified free client to achieve video recording/playback/preview
- *Support ICR filter switching function, day and night surveillance

Dimension



Accessories

- User Manual
- CD
- Screw fittings

Specification	
Product Name	H.265 5.0MP IR Dome CCTV Security Video Surveillance IP Camera
Model No.	WDM-IP8004H
Video	
System	Hisilicon high-performance DSP, (Hi3516EV100+PS5510) / (Hi3516A+Sony178,WDR) for optional
Sensor	1/3" 5.0M Pixels Progressive CMOS Image Sensor
Output resolution	2592(H)×1944(V)
D/N Mode	Auto switching ,black and white vide and IR cut action linkage
Illumination	Color 1.0Lux@F1.2,Black 0.1 Lux@F1.2
Video processing	H.265 video compression , dual streaming
	AVI format, 0.1M~6Mbps adjustable;
Video Output	Main streaming: 2592*1944,2592*1520, 2018*1536, 1920*1080,1280*960, 1280*720,1024*768,1280*720; Sub streaming: 960*540,640*360,480*270,352*288,320*240,352*192, 320*192,288*192,256*192
Frame rate	5.0MP 25/30 frame(full real time),support 1~30frame/seconds adjustable
Network interface	RJ45 ethernet, 10/100M;RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP protocol supported
Access Protocol	Standard ONVIF Protocol, Support third party access; PC;
	Support IE6.0 and aboveSmartphone
	Support Android\iPhone
Lens	
Lens	3.6/6mm lens
IR distance	15m(15pcs f5 IR leds)
Function	
Function	Support WEB configuration , OSD,real-time video transmission
	Support motion detection
	Support front end storage ,playback and download
	Support uniform client and platform system application
	Support complete SDK for second development.
Normal	
Power supply	DC12V/POE(optional)
Operation temperature	-10°C~+60°C,10%~90%RH