



- * Using the high performance sensor, image is clear and delicate;
- * Support IR-CUT dual filter switch, to achieve day and night monitoring, color is not partial and distortion;
- * AHD/TVI/CVI/1200TVL 4 in 1 video output;
- * can access to many brands HD DVR;
- * Support the ultra low illumination;
- * Support automatic electronic shutter function, adapt to different monitoring environment;
- * 30m night vision distance, 36pcs F5 ir led , DC12V
- * Metal, Waterproof IP66

Specification

Product Name	CCTV 2.0MP IR Dome HD Video Security Surveillance AHD Camera					
Model No.	WDM-AHD6352G	WDM-AHD6352S	WDM-AHD6352U	WDM-AHD6352H	WDM-AHD6352P	WDM-AHD6352K
Video						
Sensor	XM330+2235	FH8536+AR0232	V30E+Sony IMX323	NVP2441H+Sony IMX322	NVP2441H+Sony IMX291	FH8550M+Sony IMX290
Output resolution	2.0MP (1920*1080)					
D/N Mode	IR cut Auto switching					
WDR	-	-	-	-	-	Support
DNR	2D DNR	2D DNR	2D DNR	3D DNR	3D DNR	3D DNR
Minimum Illumination	0.000LUX/F1.2(Led on)					
Effective Pixel	PAL: (1920*1080)@25fps					
	NTSC: (1920*1080)@30fps					
Signal System	PAL/NTSC					
Video Standard	AHD/TVI/CVI/CVBS standard					
Video Output	1CH AHD/TVI/CVI/CVBS standard Standard Singal Output(Switchable)					
Max Transmission Distance	Common 75-3 cables can be up to 500m					
Lens and IR						
Lens	3.6mm fixed iris lens					
IR distance	30m night vision distance, 36pcs F5 ir led					
Function						
Shutter Speed	4/25s-1/45,000s					
BLC	Off/Low/Medium/High/Highest					
White Balance	Auto White Balance					
HLC	Support					
Operation Temperature	-10°C~55°C					
Power Supply	DC12V					