



Combinable HD-Cvi/Tvi/Ahd Passive CCTV UTP BNC Video Balun				
			Specifications	
			Model	WDM-UTP6011HD/A
			Transmission distance	
WDM-UTP6011HD			CVBS	1200TVL / 600M
WDM-UTP6011HDA			HD-AHD	720P/600M, 1080P/450M
<div style="background-color: #ff4500; color: white; padding: 5px; border-radius: 10px; display: inline-block;">Features</div>			HD-TVI	720P/600M, 1080P/450M, 3.0MP/350M
			HD-CVI	720P/600M, 1080P/450M
			Technical specifications	
<ul style="list-style-type: none"> * Compatible with all HD-CVI, HD-TVI, HD-AHD Cameras and analog Cameras * No power required * 60dB cross talk and noise immunity * Compact size and easy installation * Built-in transient suppression protection * Innovative combinable design * Joining by screws video transfer 			Wire Type	UTP5
			UTP Connection	"Press-Fit" terminal blocks
			Video Format	HD-CVI/TVI/AHD, NTSC, PAL, and SECAM
			Case	ABS Plastic
			Frequency Response	DC to 60MHz
			Attenuation	0.5dB typ
			CMRR	60 dB
			Surge protection	4KV
			ESD	8KV
			Power	No power required
			Working Temperature	-10°C to +50°C
			Storage Temperature	-30°C to +70°C
Humidity	0 to 95%			