



- \* Mini USB Cam driver endoscope camera
- \* Different angle lens optional
- \* 960P high resolution, image quality is brighter and clearer
- \* Very convenient and easy to use
- \* No need drive and support Win xp/Win7/Win8/Android Where to use
- \* Camera size: 30\*30mm

### Specification

Product Name	960P CCTV Mini USB Hidden Pinhole Video Surveillance Camera for ATM Machine
Model No.	WDM-U30H-MX
Sensor	1/4" 1.3MP H62; (1/3", 1/2.7" for optional)
Lens	3.7mm lens(Standard), 2.1/2.5/2.8/4.3mm for optional
Resolution	1.3MP(1280x960)/2.0MP(1920x1080) for optional
Output image format	MJPEG/YUV2(YVU)
Resolution and frame rate	320x240 OVGA MJPEG@120fps/352x288 CIF MJPEG@120fps/640x480 VGA MJPEG@120fps/1280x720P SXGA MJPEG@30fps/1028x960@30fps/1920x1080@30fps
Minimum Illumination	0.01LUX
USB protocol	USB2.0 HS/FS
Interface type	USB2.0 High Speed (Micro USB for optional)
OTG	USB2.0 OTG
No-drive protocol	USB Video Class(UVC)
ACE	Support
AEB	Support
AGC	Support
Adjustable parameter	Brightness, contrast, color saturation, clarity , sharpness, gamma, white balance, inverse contrast, exposure
Night Vision	Support, need to match infrared lens 850 or 940nm, with infrared lampboard
Power supply mode	USB BUS Power 4P-2.0mm electric outlet
Supply Voltage	DC5V
Working current	100mA-220mA
Working Temperature	0~60°
Size	30*30mm(Standard); Support custom 25*25mm, 34*34mm, 35*35mm
Supported system	WinXp/Visata/Win7/Win8, Linux with UVC(above linux-2.6.26), MAC-OS X 10.4.8 or later