


Combinable HD-Cvi/Tvi/Ahd Passive CCTV UTP BNC Video Balun		
	Specifications	
	Model	WDM-UTP3201HD
<p><b>WDM-UTP3201HD</b></p>	Transmission distance	
	CVBS	1200TVL / 600M
<p><b>Features</b></p> <ul style="list-style-type: none"> <li>* Compatible with all HD-CVI, HD-TVI, HD-AHD Cameras and analog Cameras</li> <li>* No power required</li> <li>* 60dB cross talk and noise immunity</li> <li>* Compact size and easy installation</li> <li>* Built-in transient suppression protection</li> <li>* Innovative combinable design</li> <li>* Joining by screws video transfer</li> </ul>	HD-AHD	720P/600M, 1080P/450M
	HD-TVI	720P/600M, 1080P/450M, 3.0WP/350M
	HD-CVI	720P/600M, 1080P/450M
	Technical specifications	
	Wire Type	UTP5
	UTP Connection	"Press-Fit" terminal blocks
	Video Format	HD-CVI/TVI/AHD, NTSC, PAL, and SECAM
	Case	ABS Plastic
	Frequency Response	DC to 60MHz
	Attenuation	0.5dB typ
	CMRR	60 dB
	Surge protection	4KV
	ESD	8KV
	Power	No power required
	Working Temperature	-10°C to +50°C
	Storage Temperature	-30°C to +70°C
	Humidity	0 to 95%