

8CHS WIFI NVR System with 10.1 inch LCD screen From Wardmay Professional CCTV Camera Suppliers



- \* 8CH 960P/1080P WiFi NVR with 10.1" LCD Screen
- \* Indoor/outdoor 20-30m WIFI 1.0/2-0 Megapixel IR waterproof IP cameras with adaptor, bracket.
- \* Plug and Play,no need network paring
- \* strong ability of singnal transmit up to crossing 1 to 4 walls, wifi distance:80-300 meters

\* APP: XMEye

IP Cameras specifications

|                       |                                        |                                                 |
|-----------------------|----------------------------------------|-------------------------------------------------|
| Model                 | WDM-NKITR608HDE/L-XM                   | WDM-NKITR608HDE/L-XM                            |
| Operating System      | Embedded linux                         |                                                 |
| Image Sensor          | XM510+H65 1/4" Progressive Scan Sensor | Hi3518EV200+SC2235 1/3" Progressive Scan Sensor |
| Resolution            | 960P                                   | 1080P                                           |
| Frame Specification   | H.264 1280*960@25fps                   | H.265 1920x1080@25fpS                           |
| S/N Ratio             | >39.1dB                                |                                                 |
| Minimum Illumination  | Color:0.1 Lux; B/W:0.01 Lux            |                                                 |
| Lens                  | 3.6MM                                  |                                                 |
| Infrared distance     | 20-30m                                 |                                                 |
| Waterproof            | IP66                                   |                                                 |
| White Balance         | Auto                                   |                                                 |
| Day&Night             | IR cut filter with auto switch         |                                                 |
| 3D-DNR                | Auto                                   |                                                 |
| Privacy Masking       | 8 Zone Selectable                      |                                                 |
| Infrared lamp         | 3pcs X ϕ 20 Lamp beads                 |                                                 |
| Power Input           | DC12V1A （8pcs）                         |                                                 |
| Consumption           | max 6W                                 |                                                 |
| Interface             | RJ45/WIFI 802.11b/g/n                  |                                                 |
| Operation temperature | -10°C to +50°C /30% to 80% RH          |                                                 |
| Size & Weight         | 170mm*65mm; 0.35KG                     |                                                 |

WIFI NVR Specifications

System

|                  |                                                                                         |          |
|------------------|-----------------------------------------------------------------------------------------|----------|
| Operating System | Embedded linux                                                                          |          |
| Main processor   | Hi 3520D                                                                                | Hi 3536D |
| System resources | Simultaneous multi-channel real-time recording, playback, network operation, USB backup |          |

Interface

|                    |                                                                             |         |
|--------------------|-----------------------------------------------------------------------------|---------|
| Operator interface | 16-bit true color graphic menu operation interface, support mouse operation |         |
| Preview            | 1/4/8                                                                       |         |
| Video input (IP)   | 8*960P                                                                      | 8*1080P |
| Access bandwidth   | 24Mbps                                                                      |         |

|                      |                                                            |           |
|----------------------|------------------------------------------------------------|-----------|
| Forwarding bandwidth | 25Mbps                                                     |           |
| Video compression    | H.264                                                      | H.265+    |
| Display quality      | Max 960P                                                   | Max 1080P |
| Playback quality     | 960P                                                       | 1080P     |
| Decode               | 8*960P                                                     | 2*1080P   |
| VR                   | Unsupport                                                  |           |
| Motion detection     | Support(depend on camera)                                  |           |
| Audio                |                                                            |           |
| Audio compression    | G.711A                                                     |           |
| Intercom             | Unsupport                                                  |           |
| Record & playback    |                                                            |           |
| Recording mode       | Manual>Alarm>Dynamic Detection>Timing                      |           |
| Local payback        | 8*960P/4*1080P                                             | 2*1080P   |
| Search mode          | Search by Time/Calendar/Event/Channel                      |           |
| Record storage       | HDD、Network                                                |           |
| Backup mode          | Network backup, USB hard disk, USB burner, SATA burner     |           |
| External Interface   |                                                            |           |
| Video output         | 1ch VGA, 1ch HDMI HD output                                |           |
| Audio I/O            | 0/0                                                        |           |
| Alarm I/O            | 0/0                                                        |           |
| Network interface    | 1*RJ45 10M/100M Adaptive Ethernet port+4ch WIFI            |           |
| USB interface        | 2*USB2.0 ports                                             |           |
| HDD                  | 1* SATA(Up to 8TB for each disk)                           |           |
| ESATA                | No                                                         |           |
| Serial interface     | No                                                         |           |
| Other                |                                                            |           |
| ONVIF                | No                                                         |           |
| Power supply         | 12V/2A                                                     |           |
| Power Consumption    | <10W(Without HDD)                                          |           |
| Work environment     | Temperature:0℃-+55℃ , Humidity:10%—90%RH , Atm:86kpa—106kp |           |
| Package Informations |                                                            |           |
| Wifi NVR             | 1 set                                                      |           |
| Camera               | 8 pieces                                                   |           |
| Network line         | 1m*1                                                       |           |
| Power adapter        | DC12V2A(1 pcs); DC12V1A(8 pcs)                             |           |
| USB Mouse            | 1 piece                                                    |           |
| User Manual          | 1 piece                                                    |           |
| Screw bag            | 8 pieces                                                   |           |