

Wdm CCTV H.264 1.0/2.0MP Wireless WiFi Bullet IP Camera



Features

- *Hisilicon high-performance DSP
- *High quality progressive scanning CMOS
- *H.264 High profile
- *support dual stream, support mobile phone
- *support power supply DC12V1A
- *Standard ONVIF Protocol
- *Complete SDK for second development. Support multi network protocols
- *Provide a unified free client to achieve video recording/playback/preview
- *Support ICR filter switching function, day and night surveillance

Dimension



Accessories

- User Manual
- CD
- Screw fittings

Specification		
Product Name	Wdm CCTV H.264 1.0/2.0MP Wireless WiFi Bullet IP Camera	
Model No.	WDM-IP8715A-W	WDM-IP8715R-W
Video		
System	Hisilicon high-performance DSP, Hi3518EV200+OV9732	Hisilicon high-performance DSP, 3516CV200+Sony323
Sensor	1/3" 1M Pixels Progressive CMOS Image Sensor	1/3" 2M Pixels Progressive CMOS Image Sensor
Output resolution	1280(H)×720(V)	1920(H)×1080(V)
D/N Mode	Auto switching,black and white vide and IR cut action linkage	
Illumination	Color 1.0Lux@F1.2,Black 0.1 Lux@F1.2	
Video processing	H.264 video compression, dual streaming	
	AVI format, 0.1M~6Mbps adjustable;	
Video Output	Main streaming: 1280×720,1024×768,1280×720; Sub streaming: 960×540,640×360,480×270,352×288,320×240,352×192, 320×192,288×192,256×192	Main streaming: 1920x1080, 1280x960, 1280×720,1024×768,1280×720; Sub streaming: 960×540,640×360,480×270,352×288,320×240,352×192, 320×192,288×192,256×192
	Frame rate	1.0MP 25/30 frame(full real time),support 1~30frame/seconds adjustable
Network interface	RJ45 ethernet,10/100M;RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP protocol supported	
Access Protocol	Standard ONVIF Protocol, Support third party access; PC;	
	Support IE6.0 and aboveSmartphone	
	Support AndroidiPhone	
Lens		
Lens	3.6/6mm lens	
IR distance	30m	
Function		
Function	Support WEB configuration, OSD,real-time video transmission	
	Support motion detection	
	Support front end storage ,playback and download	
	Support uniform client and platform system application	
	Support complete SDK for second development.	
	Support Wifi connection, meet with IEEE 802.11b/g wireless standard	
	Support SD Slot, max 64GB SD Card	
Normal		
Power supply	DC12V1A/POE(optional)	
Operation temperature	-10℃~+60℃,10%~90%RH	