

CCTV 4chs 2.0MP Security Surveillance Alarm DVR Systems



- * 1*4chs HD Dvr,4chs video/network;
- * 2*outdoor 30m IR waterproof AHD cameras
- * 2*indoor 30m IR Dome cameras
- * 4*18.3m(60 feet) Video+power cable
- * 1* 12v2A Power supply with 1 to 4 DC cable
- * Not included HDD

Model Number	WDM-CAHD04O-B	WDM-CAHD04P-B	WDM-CAHD04K-B
--------------	---------------	---------------	---------------

AHD Cameras specifications

Video

Sensor	NVP2441H+Sony IMX307	NVP2441H+Sony IMX291	NVP2450H+Sony IMX290
Resolution	2.0MP (1920*1080)		
Minimum Illumination	0.000LUX/F1.2(Led on)		
Day/Night Mode	Color During day/switches to B&W at night		
Signal System	PAL/NTSC		
Effective Pixel	PAL: (1920*1080)@25fps; PAL: (1920*1080)@30fps		
Video Standard	AHD/TVI/CVI/1200TVL CVBS Standard		
WDR	—	—	Yes
3D DNR	—	Yes	Yes

Lens and IR

Lens	3.6mm
IR Distance	Up to 30m
IR Cut Filter	yes

General

Waterproof	IP66
Indoor / Outdoor	Suitable for Indoor or Outdoor use
Power Input	DC12V1A (4pcs)
Working Temperature	-10°C ~+60°C

DVR Specifications

Operating System	Embedded linux
------------------	----------------

Video&Audio

Video compression	H.264
Encode	4*AHD 1080P
Analog input	4*AHD 1080P
Hybrid input	2*AHD 1080P(analog)+2*1080P(Network)
Audio Input	4 RCA Input
Audio Output	1 RCA Output
Audio compression	G.711A

Recording

Compression Format	H.264
Recording Modes	Manual/Motion/Schedule
Hard drive	Internal SATA hard drive required for recording,support up to 4TB

Network

LAN Connection	YES
Network Interface	RJ45

Interface

Video input	4ch BNC
Video output	1ch VGA, 1ch HDMI
USB	2* USB 2.0
HDD	1*SATA port (Max 4TB/per)

General

Power Supply	DC 12V
Back up method	External storage via USB
Temperature/Humidity	-20°C+50°C; -10%-90%
Remote Control	YES

DVR Language

Russian, English, Finnish, French, German, Greek, Italian, Japanese, Poland, Protugal, Spanish, Thai, Turkey Romanian, Slovakia, Czech, Arabic, Swedish and so on