

沃德镁 IHD CCTFV Total Solution

www.wardmay.com

304 Stainless Steel Explosion-Proof CCT	/ Mini Camera For M	arine, Gas Station	
Notice	Camera		
	Model	WDM-EX700MA	WDM-EX200HA
	Sensor	Color 1/3" CCD	Color 1/3" CMOS IMX322
	System	PAL/NTSC	
	Resolution	700TVL	1080P
	Effective pixels	PAL: 795(H)×596(V) / NTSC: 811(H) * 508(V)	1920*1080
CEFC 🧟 www.wardmay.com	S/N Ratio	52dB(Min)/60dB(Max)(AGC ON/OFF)	52dB(Min)/60dB(Max)(AGC ON/OFF
Features	Lens	4/6mm lens for optional	
* 700/1080P High Resolution	IR LED	36PCS IR LEDS	
* 4/6mm lens for optional	IR Distance	15-20m night vision distance	
* Explosion-proof housing	Signal-to-Noise Ratio	>75db	
* 304 stainless steel surface treated with fluorine-	Electrical Connectivity	Composite cable	
carbon spray. elegant structure. explosion proof, dust proof,	Rated Temperature	-30 degree ~ +70 degree	
water proof, rust-proof	Atmospheric Pressure	86~106kpa	
* Optics class toughened ultra clear white	Relative Humidity	<=95%RH(+-25 degree)	
explosion proof glass, flux rate higher than 96%	Dimension	132*117*150mm	
* Optional temperature controlled SCR	Material	304 Stainless steel	
semiconductor module to realize automatic	Ingress Protection	IP66	
heating and cooling functionsheater turned on	Interface spec	G-1/2"	
when temperature lower than -10 degree +-5 degree	Method of installation	bracket mount	
* Can be installed on the market 80% camera	Atex Mark	II 2G Ex db IIC T6 Gb, II 2D Ex tb IIIC(85 degree) Db	
* We can customize right camera size according	IEC Mark	Ex dIIC T6 Gb/DIP A20 TA, T6	
to your requirement	Input Voltage	DC12V	
	Working Current	<=1A	