



- * Support 32ch 4M unreal-time encoding
- * Support Xvi,AHD, TVI,CVI, CVBS, IP video input
- * Support VGA maximum 1080P output, HDMI up to 4K output
- * Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc
- * Support the Onvif protocol
- * Support WEB, CMS, VMS, MYEYE Platform
- * Mobile phone remote monitoring (iOS, Android)
- * Cloud services, P2P, alarm information push to phone
- * Support for more than twenty languages

Specifications

Product Name	32chs 4.0MP Network AHD DVR
Model No.	WDM-DVR6532F-GS

System

Processor	Hi3531A
-----------	---------

Video

Video compression	H.265X/H.264
Encode	32*4M@8fps(AHD); 32*3M@10fps(AHD); 32*1080P @15fps (5 in 1) ; 32*720P(5 in 1)
Decode	16*4M@8fps(AHD); 16*3M@10fps(AHD); 16*1080P @15fps (5 in 1) ; 16*720P(5 in 1)
preview	32*4M@15fps(AHD); 32*3M@18fps(AHD); 32*1080P (5 in 1)
Multi-mode	Analog: 32*4M@8fps(AHD); 32*3M@10fps(AHD); 32*1080P @15fps (5 in 1) ; 32*720P(5 in 1)
	Hybird: 16*4M+16*4M
	IP: 32*1080P;16*3M ;8*5M
Playback	16ch

Audio

Audio compression	G.711A
Intercom	Support

Management

Record mode	Manual>Alarm>Motion detection>Timing
Inquire mode	Inquire by Time/Calendar/Event/Channel
Storage mode	HDD Storage, Network Storage
Backup	Network, USB, SATA

Interface

Video Input	32*BNC (Support Coaxitron)
HDMI output	1*HDMI (MAX:4K)
VGA output	1*VGA (MAX:1080P)
Audio In/Out	16/1
Alarm In/Out	16/4
Ethernet	1*10/100Mbps Ethernet port, RJ45 port
PTZ Control	1*RS485, Support for multiple PTZ protocol
USB	2*USB2.0 ports
HDD	4*SATA interface (Up to 6TB)

General

Power supply	12V/6A
Consumption	<10W (Without HDD)
Working temperature	0 ℃ - + 55 ℃
Working humidity	10% -90% RH
Chassis	Mini 1.5U