



- * Hisilicon high-performance DSP
- * High quality progressive scanning CMOS
- * H.264 High profile
- * support dual stream, support mobile phone
- * Complete SDK for second development. Support multi network protocols
- * Standard ONVIF Protocol
- * Provide a unified free client to achieve video recording/playback/preview
- * Support ICR filter switching function, day and night surveillance
- * **APP: XMEYE**

Specification

Product Name	Wdm Security 1.0/1.3/2.0MP Fire Sprinkler Hidden Full HD Mirror IP Camera		
Model No.	WDM-IP64PTA	WDM-IP64PTB	WDM-IP64PTH
Video			
System	Hisilicon high-performance DSP, HI3518E+OV9732	Hisilicon high-performance DSP, HI3518E+AR0130	Hisilicon high-performance DSP, HI3518E+SC2235
Sensor	1/4" 1.0M Pixels Progressive CMOS Image Sensor	1/3" 1.3M Pixels Progressive CMOS Image Sensor	1/3" 2.0M Pixels Progressive CMOS Image Sensor
Output resolution	1280(H)x720(V)	1280(H)x960(V)	1920(H)x1080(V)
D/N Mode	Auto switching, black and white vide and IR cut action linkage		
Illumination	0.1Lux @(F1.2, AGC ON), 0 LUX		
Video processing	H.264 video compression, dual streaming		H.265 video compression, dual streaming
	AVI format, 0.1M~6Mbps adjustable;		
Video Output	Main streaming: 1280×720, 1024×768, 1280×720; Sub streaming: 960×540, 640×360, 480×270, 352×288, 320×240, 352×192, 320×192, 288×192, 256×192	Main streaming: 1280×960, 1280×720, 1024×768, 1280×720; Sub streaming: 960×540, 640×360, 480×270, 352×288, 320×240, 352×192, 320×192, 288×192, 256×192	Main streaming: 1920×1080, 1280×960, 1280×720, 1024×768, 1280×720 Sub streaming: 960×540, 640×360, 480×270, 352×288, 320×240, 352×192, 320×192, 288×192, 256×192
Audio input	Optional		
Audio Format	G.711/G.726		
Frame rate	1.0MP 25/30 frame(full real time), support 1~30frame/seconds adjustable	1.3MP 25/30 frame(full real time), support 1~30frame/seconds adjustable	2.0MP 25/30 frame(full real time), support 1~30frame/seconds adjustable
Network interface	RJ45 ethernet, 10/100M; RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP protocol supported		
Access Protocol	Standard ONVIF Protocol, Support third party access; PC;		
	Support IE6.0 and above Smartphone		
	Support Android\iPhone		
Lens			
Lens	3.7mm lens(standard)		
Function			
Function	Support WEB configuration, OSD, real-time video transmission		
	Support motion detection		
	Support front end storage , playback and download		
	Support uniform client and platform system application		
	Support complete SDK for second development.		
Normal			
Power supply	DC12V/POE(optional)		
Operation temperature	-10°C~+60°C, 10%~90%RH		