

**H.265 10X 2.0MP CCTV Video Surveillance IR Bullet IP HD Camera**



**Features**

- \*Hisilicon high-performance DSP
- \*High quality progressive scanning CMOS
- \*H.265 High profile
- \*support dual stream, support mobile phone
- \*support power supply DC12V/POE
- \*Standard ONVIF Protocol
- \*Complete SDK for second development. Support multi network protocols
- \*Provide a unified free client to achieve video recording/playback/preview
- \*Support ICR filter switching function, day and night surveillance
- \*Waterproof IP66

**Dimension**



**Accessories**

- User Manual
- CD
- Screw fittings

Specification	
Product Name	<b>H.265 10X 2.0MP CCTV Video Surveillance IR Bullet IP HD Camera</b>
Model No.	WDM-IP8001TZ
Video	
System	Hisilicon high-performance DSP, (Hi3516D+Sony IMX 290, Super WDR)
Sensor	1/3" 2.0M Pixels Progressive CMOS Image Sensor
Output resolution	1920(H)×1080(V)
D/N Mode	Auto switching,black and white vide and IR cut action linkage
Illumination	Color 1.0Lux@F1.2,Black 0.1 Lux@F1.2
Video processing	H.265 video compression, dual streaming AVI format, 0.1M~6Mbps adjustable;
Video Output	Main streaming: 1920*1080, 1280*960, 1280×720,1024×768,1280×720; Sub streaming: 960×540,640×360,480×270,352×288,320×240,352×192, 320×192,288×192,256×192
Frame rate	2.0MP 25/30 frame(full real time),support 1~30frame/seconds adjustable
Network interface	RJ45 ethernet, 10/100M;RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP protocol supported
Access Protocol	Standard ONVIF Protocol, Support third party access; PC; Support IE6.0 and aboveSmartphone Support Android\iPhone
Lens	
Lens	5-50mm auto iris lens
IR distance	80m(4pcs 42mil Array)
Function	
Function	Support WEB configuration, OSD,real-time video transmission Support motion detection Support front end storage ,playback and download Support uniform client and platform system application Support complete SDK for second development.
Normal	
Power supply	DC12V/POE(optional)
Operation temperature	-10°C~+60°C,10%~90%RH