

**CCTV 2.0MP IR Bullet Video Surveillance HD IP Security Camera**



**Features**

- \*Hisilicon high-performance DSP
- \*High quality progressive scanning CMOS
- \*H.264 High profile
- \*support dual stream, support mobile phone
- \*support power supply DC12V/POE
- \*Standard ONVIF Protocol
- \*Complete SDK for second development. Support multi network protocols
- \*Provide a unified free client to achieve video recording/playback/preview
- \*Support ICR filter switching function, day and night surveillance
- \*Waterproof IP66

**Dimension**



**Accessories**

- User Manual
- CD
- Screw fittings

| Specification         |   |
|-----------------------|---|
| Product Name          | <b>CCTV 2.0MP IR Bullet Video Surveillance HD IP Camera</b>   |
| Model No.             | WDM-IP7738R   |
| Video                 |   |
| System                | Hisilicon high-performance DSP, Hi3516EV100+2235P;Hi3516EV100+Sony IMX323;Hi3516EV100+SonyIMX307,DWDR;Hi3516CV300+Sony290,WDR         |
| Sensor                | 1/3" 2.0M Pixels Progressive CMOS Image Sensor  |
| Output resolution     | 1920(H)×1080(V)   |
| D/N Mode              | Auto switching,black and white vide and IR cut action linkage   |
| Illumination          | Color 1.0Lux@F1.2,Black 0.1 Lux@F1.2  |
| Video processing      | H.264 video compression , dual streaming  |
|                       | AVI format, 0.1M~6Mbps adjustable;  |
| Video Output          | Main streaming: 1280×720,1024×768,1280×720;<br>Sub streaming: 960×540,640×360,480×270,352×288,320×240,352×192,320×192,288×192,256×192 |
| Frame rate            | 2.0MP 25/30 frame(full real time),support 1~30frame/seconds adjustable  |
| Network interface     | RJ45 ethernet,10/100M;RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP protocol supported  |
| Access Protocol       | Standard ONVIF Protocol, Support third party access; PC;  |
|                       | Support IE6.0 and aboveSmartphone   |
|                       | Support Android\iPhone  |
| Lens                  |   |
| Lens                  | 2.8-12mm varifocal lens   |
| IR distance           | 50m(2pcs 42mil Aarray ir leds)  |
| Function              |   |
| Function              | Support WEB configuration, OSD,real-time video transmission   |
|                       | Support motion detection  |
|                       | Support front end storage ,playback and download  |
|                       | Support uniform client and platform system application  |
|                       | Support complete SDK for second development.  |
| Normal                |   |
| Power supply          | DC12V/POE(optional)   |
| Operation temperature | -10°C~+60°C,10%~90%RH   |