



- \* Support 4/8CH 8.0MP Encoding
- \* Support XVI,AHD, TVI,CVI, CVBS, IP video input
- \* Support VGA maximum 1080P output, HDMI up to 4K output
- \* Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc
- Support the Onvif protocol
- Support WEB, CMS, VMS, MYEYE Platform
- Mobile phone remote monitoring (iOS, Android)
- \* Cloud services, P2P, alarm information push to phone
- \* Support for more than twenty languages

### Specifications

Product Name	4/8chs H.265+ 6 In 1 4K Network AHD DVR	
Model No.	WDM-DVR6504K-N	WDM-DVR6508K-N

### System

Processor	Hi3520DV400	Hi3521D
-----------	-------------	---------

### Video

Video compression	H.265+	
Encode	4*4K-N@15fps(6 in 1), 4*5M@12fps(6 in 1), 4*4M@15fps(6 in 1), 4*3M@18fps(6 in 1), 4*1080P(6 in 1)	8*4K-N@15fps(6 in 1), 8*5M@12fps(6 in 1), 8*4M@15fps(6 in 1), 8*3M@18fps(6 in 1), 8*1080P(6 in 1)
Decode	4*4K-N@15fps(6 in 1), 4*5M@12fps(6 in 1), 4*4M@15fps(6 in 1), 4*3M@18fps(6 in 1), 4*1080P(6 in 1)	8*4K-N@15fps(6 in 1), 8*5M@12fps(6 in 1), 8*4M@15fps(6 in 1), 8*3M@18fps(6 in 1), 8*1080P(6 in 1)
Multi-mode	Analog: 4*5MP/8MP(same channel, adaptive 8MP), 4*4MP	Analog: 8*5MP/8MP(same channel, adaptive 8MP), 8*4MP
	Hybird: 4*4MP(analog)+4*4MP(IP)	Hybird: 8*4MP(analog)+8*4MP(IP), 4*4MP(analog)+4*4MP(IP)
	IP: 16*1080P,8*5MP	IP: 8*1080P+8*960P, 4*5MP,4*3MP
Playback	4ch	8ch

### Audio

Audio compression	G.711A
-------------------	--------

### Management

Record mode	Manual>Alarm>Motion detection>Timing
Inquire mode	Inquire by Time/Calendar/Event/Channel
Storage mode	HDD Storage, Network Storage
Backup	Network, USB, SATA

### Interface

Video Input	4*BNC (Support Coaxitron)	8*BNC (Support Coaxitron)
HDMI output	1*HDMI (MAX:4K)	
VGA output	1*VGA (MAX:1080P)	
Audio In/Out	4/1	4/1
Alarm In/Out	0/0	
Ethernet	1*10/100Mbps Ethernet port, RJ45 port	
PTZ Control	1*RS485, Support for multiple PTZ protocol	
USB	2*USB2.0	
HDD	1*SATA interface (Up to 8TB)	

### General

Power supply	DC12V 4A
Consumption	<15W(Without HDD)
Working temperature	0℃--+55℃
Working humidity	10%--90%
Chassis	168mm*80mm