

Wdm CCTV H.264 1.0/1.3/2.0MP Wireless WiFi Bullet IP Camera



Features

- *Hisilicon high-performance DSP
- *High quality progressive scanning CMOS
- *H.264 High profile
- *support dual stream, support mobile phone
- *support power supply DC12V1A
- *Standard ONVIF Protocol
- *Complete SDK for second development. Support multi network protocols
- *Provide a unified free client to achieve video recording/playback/preview
- *Support ICR filter switching function, day and night surveillance

Dimension



Accessories

- User Manual
- CD
- Screw fittings

Specification			
Product Name	Wdm CCTV H.264 1.0/1.3/2.0MP Wireless WiFi Bullet IP Camera		
Model No.	WDM-IP8004A-W	WDM-IP8004B-W	WDM-IP8004R-W
Video			
System	Hisilicon high-performance DSP, Hi3518EV200+OV9732	Hisilicon high-performance DSP, Hi3518EV200+SC1135	Hisilicon high-performance DSP, 3516CV200+Sony323
Sensor	1/3" 1M Pixels Progressive CMOS Image Sensor	1/3" 1.3M Pixels Progressive CMOS	1/3" 2M Pixels Progressive CMOS Image Sensor
Output resolution	1280(H)×720(V)	1280(H)×960(V)	1920(H)×1080(V)
D/N Mode	Auto switching,black and white vide and IR cut action linkage		
Illumination	Color 1.0Lux@F1.2,Black 0.1 Lux@F1.2		
Video processing	H.264 video compression, dual streaming		
	AVI format, 0.1M~6Mbps adjustable;		
Video Output	Main streaming: 1280×720,1024×768,1280×720; Sub streaming: 960×540,640×360,480×270,352×288,320×240,352×192,320×192,288×192,256×192	Main streaming: 1280×960,1280×960,1024×768,1280×720; Sub streaming: 960×540,640×360,480×270,352×288,320×240,352×192,320×192,288×192,256×192	Main streaming: 1920x1080, 1280x960, 1280x720,1024*768,1280*720; Sub streaming: 960×540,640×360,480×270,352×288,320×240,352×192,320×192,288×192,256×192
	1.0MP 25/30 frame(full real time),support 1~30frame/seconds adjustable	1.3MP 25/30 frame(full real time),support 1~30frame/seconds adjustable	2.0MP 25/30 frame(full real time),support 1~30frame/seconds adjustable
Network interface	RJ45 ethernet,10/100M;RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP protocol supported		
Access Protocol	Standard ONVIF Protocol, Support third party access; PC;		
	Support IE6.0 and aboveSmartphone		
	Support Android/iPhone		
Lens			
Lens	3.6/6mm lens		
IR distance	30m		
Function			
Function	Support WEB configuration, OSD,real-time video transmission		
	Support motion detection		
	Support front end storage ,playback and download		
	Support uniform client and platform system application		
	Support complete SDK for second development.		
	Support Wifi connection, meet with IEEE 802.11b/g wireless standard		
Support SD Slot, max 64GB SD Card			
Normal			
Power supply	DC12V 1A/POE(optional)		
Operation temperature	-10°C~+60°C,10%~90%RH		