

4CHS H.264 720P HD 4 In 1 MDVR



FEATURES:

- * Built-in high performance Hisilicon chipsets, coded with H.264 standard, high compression rate and image quality
- * 4CH AV Inputs with AHD 720P/960H/D1/CIF optional, 1CH synchronized AV output, Scalable 1CH VGA output
- * 4CH local recording with 720P resolution in real time

Power:

- * Professional In-Vehicle power design, 9-36V DC Wide Voltage Range
- * Multi protection circuits like under-voltage, short, reversed plug-in
- * Smart power management system, shutdown under low voltage, low consumption when standby

Data Storage:

- * Special file management system to encrypt and protect the data
- * Proprietary technology to detect the bad track of the SD card which can make sure the continuity of video and long service life of the SD card
- * Built-in ultracapacitor, avoid data loss and sd card damage caused by sudden outage
- * Support SD card storage, maximum 256G

Item	Device parameter	Performance
System	Model Number	WDM-MDVR8504B(Series)
	Operating system	Embedded Linux OS (Hi3520DV200)
	Operating language	Chinese/English
	Password security	User password/Admin password
Audio & Video	Video standard	PAL/NTSC
	Video compression	H.264
	Image resolution	720P /960H/D1/CIF
	Playback quality	720P /960H/D1/CIF
	Compound mode	4ch 720P/4ch 960H/2ch 720P+2ch 960H
	Decoding ability	1ch 720P real time
	Recording quality	Class 1-6 optional
	Image display	Single/QUAD display optional
	Audio Compression	G.726
	Audio recording	Audio & Video synchronized recording
Recording & Playback	Recording mode	Manual/Alarm
	Video bit rate	Full frame 4096Mbps, 6 classes image quality optional
	Audio bit rate	8KB/s
	Storage media	SD card storage
	Local playback	Playback by file
Firmware upgrading	Upgrading mode	Manual/Automatical
	Upgrading method	USB disk/Wireless network
Interface	AV input	4ch aviation interface
	AV output	1ch aviation AV output, Scalable 1ch VGA output(Standard without VGA output)
	Alarm	4chs digital inputs,(2 Positive trigger, 2 negative trigger); 1chs digital outputs
	SD card	1 SDXC High speed card (up to 256G)
	USB interface	1 USB 2.0 (support U disk/mouse)
	Ignition input	1 ACC signal
	UART	1 LVTTTL Level
	SD card lock	1
	Debug port	1
Expand Functions	1. GPS	Optional
	2. GPS+Wifi	Optional
	3. GPS+3G/4G	Optional
	4. GPS+Wifi+3G/4G	Optional
Others	Power input	9~36V DC
	Power consumption	Standby 3mA Maximum consumption 18W @12V 1.5A @24V 0.75A
	Power output	5V 300mA
	Working temperature	-20 --- 70℃
	Storage	720H 1G/h/channel, 960H/h/channel