

DWB-500G HIGH SPEED RECIPROCATING PILLOW TYPE PACKING MACHINE

QUOTATION

Name/ description	Qty.	Unit price/USD	Agent price/USD	备注
DWB-500G HIGH SPEED RECIPROCATING PILLOW TYPE PACKING MACHINE Including : 1) Blister servo motor feeder 2) Hot ink printer	set	\$52450.00/FOB	\$47,200USD/FOB	
The accelerating device for connecting blister packing machine	Set	\$2500	\$2500	

Notice:

1. price item: **FOB NINGBO PORT OF CHINA**
2. Payment: 30% deposit by T/T in advance. 70% before shipping.
3. Delivery time: after received 30% deposit delivery within 45 days.
4. The price not including install machine fee. If need our technician go to install machine and trading workers, the buy should pay all fee (round-trip ticket, hotel, food, visa and salary)
5. Guarantee: 12 monthes.

details about machine please check the files





accelerating device for connecting blister packing machine

FEATURES

- 1) Main machine use steeples speed change device and three servo motor drive—**
high speed 130bags/min (Metalize,Aluminum Foil 80 micron).
Suitable for various packing materials
- 2)Reciprocating sealing --** Seal stronger, sealed die - cut knife Lossless, bag - shaped more beautiful
- 3) Eliminating detection**
A)Packaging film tape connector automatically detect removed
B)Code printer leakage printing Eliminating
C)blisters short or multi automatically detect removed
D)Film finish give alarm and stop machine
- 4)Ethernet remote control**—Can modify the problem.Facilitate management, human resource conservation
- 5) Menu and memory function**
- 6)PLC control**
- 7)Touch screen** –show the speed,setting length ,the actual length ,yield
- 8)Length of bag automatic adjust**--seting the length on the touch screen,machine automatic adjust
- 9)Two-way compensation on the subject** –Import of Photoelectric detection sensor and detection of color mark ,by the PLC computer programs combined with Bi-directional compensation agency,automatic tracking.More stanard fast and accurate.
- 10)6 group temperature control**-Each heating position adopt autoamtic temperature control,it can be set on the touch screen,improving the quality of the seal.
- 11)Adjustable bag former**-suitable for various size of bag.
- 12)Servo motor blister feeder**-can be set from 1-5blisters

MAIN TECHNICAL PARAMETERS

Production capacity	110-130bags/min (blister length about 120mm , vary with different specifications)
Max. film width	450mm
Cut off length	80-300mm
Bag size	L60-200mm,W:35-200mm H5-55mm
Rated frequency	50Hz
Rated voltage	220V
Air compressor	>0.15 CBM/min
Total power	4.2KW
Machine weight	about1300kg
Overall dimension	LxWxH 3750x1200x1700mm

DWB-500G HIGH SPEED RECIPROCATING PILLOW TYPE PACKING MACHINE

ACCESSORY LIST

1	Electric apparatus	Programmable controller: with PLC of Panasonic 10 inch touch screen of Taiwan Weinniew
2	Transporting part	Adopt transporting belt imported
3	Driving part	steeple speed change device and three servo motor drive control feed,traction,cut.
4	Machine cover	Full stainless steel 304
5	Machinery parts	To made in our factory

Name	From	Specification
Cross sealing belt	Xiamen xinbex	8M-920
Sponge belt	Xiamen xinbex	750×180
Belt	Xiamen xinbex	1290×180×0.4 1705×180×0.4
Cutter	Shanghai	
Thermocouple	Shanghai Yatai	¢3×40
Concave photo electrical	Japan (OMRON)	ZZ-Sx670A
Feeder servo motor	Japan YASKAWA	0.4KW
Power switch	Taiwan Weinniew	S-50-24
Photo E-mark sensor	Shanghai Yatai	GDJ-211
Heater	Jiangsu	¢8×250 300W 220V ¢10×85 200W 220V
Three servo motor (feed,traction,cut.)	Japan Panasonic	3×0.75KW
Solid reply	Wenzhou huanan	220D25
midget relay	Japan (OMRON)	MY2N (24VDC)
electromagnet	Zhejiang huaxin	MFBI-2.5YC220V
PLC	Japan Panasonic	