


#### CANGZHOU ZHONGTUO COLD ROLL FORMING MACHINERY

Room 807, Building 6, Taida International, Yunhe district, Cangzhou City, Hebei province, China Contact: Vivian Tel:+86 18730769688 QQ:2087793513 Skype: cnzt005@zhongtuocn.com

### 60-27-28 roll forming machine

### **Customer drawing profile:**



Thickness: 0.3-0.7mm

S/N	Name	Parameter	Pictures
1	Decoiler	Usage: It is used to support the steel coil and uncoil it in a turntable way.  Passive uncoil pulled by roll forming system  Loading capacity: 1.5T  Uncoiling width: 300mm  Inner diameter: 450-550mm	
2	Feeding and leveling	Usage: Put the raw material(steel plate) through the beach to manufacture and process, it can guarantee that the products are neat, parallel and everything is uniformity. Please refer to the equipment regulation to know the function of locate angle iron	



#### CANGZHOU ZHONGTUO COLD ROLL FORMING MACHINERY

Com	tact: Vivian Tel:+86	18730769688 QQ:2087793513 Skype: c	nzt005@zhongtuocn.com
3	Roll forming machine	Size: 3000 × 1000 × 1400mm  Weight t: 3tons  Voltage:380V/50HZ3Phase(as customer's request)  Frame: middle plate welded  Memorial arch frame type  Frame thickness:25mm  Drive mode: gear  Material of rollers: GCr12MoV  Material of shafts: 45# steel with tempering  Diameter of shafts: Φ 40mm  Number of rollers: 10 rollers  Main power: 3kw  Speed: 25m/min  Cycloidal planetary gear speed reducer)	
5	Shearing machine	Material of blades: Gcr12 quenched Power supply: hydraulic power Frame: Pillar style with rack & pinion system Stroke switch: non-contact photoelectric switch	



#### CANGZHOU ZHONGTUO COLD ROLL FORMING MACHINERY

6	Hydraulic Station	Hydraulic motor Power: 3kw Hydraulic oil: 46# Components: The system includes a set of hydraulic tank, a set of hydraulic oil pump, and two hydraulic pipes. And two sets of electromagnetism valves.			
7	Electric Control System	Feature:  1. Adopted PLC, transducer, touch panel from Delta Taiwan to ensure high speed with stability, precision and lifetime.  2. Other electric element are Delta  3. Equipped with movable switch, air break, radiator, transformer & electric leakage protector for operation convenience and safety.	A SECTION OF SECTION O		
8	Run-out table	It adopts welded steel and supported roller to transmit the products.			
9	Price: USD8500 /LIN	NE FOB XINGANGCHINA			
	Payment: 30% T/T i	Payment: 30% T/T in advance and balance 70% after inspection confirmation before shipment.			
10	<ol> <li>One year, and we will provide the technical support for the whole life.</li> <li>Training: the buyer should charge of visa, return ticket, food and accommodation overseas and USD50/person/day for salary.</li> <li>Need one technicians.</li> </ol>				
	4. Training time: on	d adjustment)			

## \*\*\*\*沧州中拓冷穹成型设备制造商

#### CANGZHOU ZHONGTUO COLD ROLL FORMING MACHINERY





# 沧州中拓冷弯成型设备制造商

#### CANGZHOU ZHONGTUO COLD ROLL FORMING MACHINERY





# \*\*\*\*\*\*\*\*\*\*\*沧州中拓冷穹成型设备制造商

#### CANGZHOU ZHONGTUO COLD ROLL FORMING MACHINERY

