

Model	HAE-6000 Thermal Inkjet Coder
Print system	HP TIJ2.5
Print height	HAE-6000-1: 12.7mm
	HAE-6000-2: 2*12.7mm
	HAE-6000-3: 3*12.7mm
	HAE-6000-4: 4*12.7mm
Max print speed&Resolution	30 m/m@ 600×600DPI
	60m/m@300×300DPI
	120m/m@300×150DPI
Port	USB/ RS232/Multi functional interface
Display screen	10.1 inch touchable screen
Operation interface	EASYTOUCH
Font size	TrueType zoom
Template format	LGPV1.0
Print data type	Text, counter, date, barcode, image ,database
Barcode type	EAN8 EAN13 EAN128 CODE25 CODE39 CODE128 CODE128A CODE128B CODE128C Codebar2width UPC12 PIATS
supported	PIATSDRUG QRCODE DATAMATRIX
Real time data	Counter, date ,barcode ,text ,image, database
Other	Simulation speed print/Simulation sensor print
Power supply	110-220VAC 50/60Hz
Max power	120W
Operation temperature & humidity	TEM 5°C~35°C HUM 10%~90%
Package dimension	302*229*210mm(L*W*H)
Package weight	3.9Kg/1HEAD 4.3Kg/2HEAD 4.8Kg/3HEAD 5.3Kg/4HEAD