

## SPECIFICATION

Belt type	Fabric type	Single fabric strength (N/mm)	Single fabric thickness(mm)	Rubber cover thickness(mm)		Ply	Belt width range(mm)	Belt length(m)/roll
				Top	Bottom			
Cotton Canvas( CC) conveyor belt	CC-56	56	1.10	3.0/4.5/6.0	1.5/3	3-12	500-2200	100-1000
Nylon conveyor belt	NN100	100	0.70			2-10		
	NN150	150	0.75			2-6		
	NN200	200	0.90					
	NN250	250	1.15					
	NN300	300	1.25					
	NN400	400	1.50					
Polyester(EP) conveyor belt	EP100	100	1			2-10		
	EP125	125	1			2-6		
	EP150	150	1.1					
	EP200	200	1.2					
	EP250	250	1.4					
	EP300	300	1.5					
	EP400	400	1.65					

Cover rubber grade&Standard NO.

Standard NO.		Cover rubber		
		Tensile strength(MPA )	Elongation at break(%)	Abrasion( mm3)
DIN22102	Z	15	350	250
	W	18	400	90
	Y	20	400	150
	X	25	450	120
SANS1173	A	18	400	90
	X	25	450	120
	M	24	450	150
	N	20	400	250
RMA	I	17	400	-
	II	14	400	-
AS1332	N17	17	400	200
	N24	24	450	125

### Quality Warranty Period:

1.General belts:warranty period is 12months.

2.Heat resistant belt:

a.if the temperature of the material is 180degrees,the warranty period is only 6months.

b.if the temperature of the material is more than 200degree,the warranty period is only 3months.

3.The belt is used in cement plant,warranty period is only 3months.

If there is a cracking phenomenon during use,it does not belong to quality problems.

4.The belt is used in steel plant,warranty period is only 1months.

5.NOTE:The service life of the conveyor belt depend on the actual operation ambient.

### PACKING:

1.STEEL CORE+BLUE SIDE DISKS+WHITE PP CLOTH

2.PALLET

3.CUSTOMIZED

MARKING DRAWING ON BELT IS AVAILABLE.