

## 高周波塑胶熔断机系列

### High Frequency Welding and Cutting Machine Series



CH-8KW-TPRD



CH-8KW-YPRD

型号 Model	CH-8KW-TPRD	CH-8KW-YPRD
输出功率 Output Power	8KW	8KW
电压 Voltage	220V/380V 3P 50/60HZ	220V/380V 3P 50/60HZ
电源入力 Input Power	10KVA	10KVA
振荡频率 Oscillation Frequency	27.12MHZ	27.12MHZ
震荡管 Oscillation Tube	7T69RB	7T69RB
防火花系统 Anti-Spark System	NL-5557	NL-5557
最大压力 Max Pressure	10TON	10TON
上下电极间隔 Gap of Electrode	200mm	200mm
上压板尺寸 Size of Mould Holder	350*450	420*560
工作台面尺寸 Working Table Size	350*450	420*560
机器尺寸 Machine Size	2200*1450*2300mm	1320*1740*2300mm
机器重量 Machine Weight	1500KG	1500KG

#### 机器特点:

高灵敏度美国原装双管火花保护装置，能有效保护模具及产品之缺损，从而大大减少烧坏模具机率，采用国际大品牌原装 OMRON（欧姆龙）继电器及台湾正宗 CKC 时间制，能保证机器长时间的频率工作，并大大延长机器寿命，减少机器故障。

#### Feature:

Using high sensitivity America-Imported anti-spark triode tube, which is useful for protect mould and products once machine over current. Adopting famous brand OMRON relay and CKC timer, greatly extend the life of the machine, reduce the machine failure.